Namo of work: G1364 20. 10 2139 110128 SHEW # 20 25=>126) 6724

S.N	Description and details of		PWD building S	
ο.	Description and details of work	unit	Qty.	
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area).	Curn	3.84	1
	Providing and laying nominal mix plain coment concrete with crushed alone aggregate using concrete mixer in all works upto plain level excluding cost or form work.  1.4:8 (1 coment: 4 coarse sand: 8 graded stone aggregate 40mm nominal size).	Cum	0.38	
	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1.5:3 (1 coment: 1.5 coarse sand: 3 graded stone aggregate 40mm nominal size).	Cum	3.46	194
i i i i i i i i i i i i i i i i i i i	Supply, erection, jointing, testing & commissioning of "C" Class MS pipes (as per IS: 1239) including necessary specials such as ees, bends, langes reducers etc., complete on wall/ ceiling. The pipes to be erected on wall or suspended from beams, RCC roof slabs with suitable size MS pars/ angle irons including pointing of metal part except pipe line.	m	- 30.00	
sa c 2 b n n trust o p d	Supply and fixing of precoated galvanized iron profile theets (size, shape and pitch of corrugation as ppfoved by Engineer-in-charge) 0.50 mm +/-5% total oated thickness (TCT), Zinc coating 120gsm as per IS: 77 in 240mpa steet grade, 5-7 microns epoxy primer on oth side of the sheet and polyester top coat 15-18 nicrons. Sheet should have protective guard film of 25 nicrons minimum to avoid scratches while ansportation and should be supplied in single length per coat 12 metre or as desired by Engineer-in-charge. The heet shall be fixed using self drilling /selftapping screws I size (5.5x 55mm) with EPDM seat or with olymercoated J or L hooks, botts and nuts 8mm ameter with bitumen and G.I.limpet washers or with	Sqm	130.00	
G Br ED	Itimpet washers filled with white lead complete upto ny pitch in horizontal/vertical or curved surfaces actuding the costof purlins, rafters and trusses and cluding cutting to size and shapewherever required.			
	6			
13	- Pa			
		Sqm	26.00	-
		and the second s	200,00	

6	Structural steel work riveted or botted or welded in built- up sections trusses and frames work upto a height of 5m above plinth level, including cutting, hoisting, fixing in postics and applying a priming cost of red exide	kg ,	1390,00
7	"Extra for hoisting trasses and placing in position over height above 5m for avery 2.5 m height or part thereof."	kg	1300.00
8	"Providing 40x5mm iron hold fast 40cm long including fixing to frame with 10mm bolts nuts and wooden plug and embedding in Cement Concrete	kg	25.00
9	Painting on new work (two or more coats) to give an even shade with: 14.22.1 Satin synthetic enamel paint	sqm	40.00
10	Extra for providing and lixing wind ties of 40x6mm flat iron section ;	m	78,00
11	Structural steel work in single section including cutting, hoisting, lixing in position and applying a priming cost of red exide zinc chromate primer.	kg	150.00
	Brick work with modular fly-ash time bricks (FatG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in	Cum	3.10
1.3	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix:	sqm	6.490

कार्यपालका अभिरांता अनुविभाग क्रमांक ६ सेवटर-६ मगर पालिक निगम भिलाई

सहायक अभियंत्रा अनुविभाग क्रमांक ५ सेवटर-६ भगर पालिक निवम भिलाई

उसे अश्विरांता अणुविभाग क्रमांक ६ सेयटर-६. ज्ञार पालिक जिमम भिसर्ज