MUNICIPAL CORPORATION OF BHILAI

वार्ड 48, सेक्टर 01, क्रास स्ट्रीट में मंदिर के समीप संघारण कार्य।

As Per PWD Building SOR 01.01.2015

	s.	TARTE OBERS OF TEMS	Quantity	UOM
	1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soils.	10.501	Cum
	2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	16.31	Cum
		Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.	57.65	Cum
	4 8	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement: 6 coarse and)Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth:	13.55	Cum
	ti	roviding and making 12mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 ne sand)	44.40	Sqm
	st	ement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded one aggregate 20mm) finished with a floating coat of neat cement.50 mm thick	118.95	Sqm
	7 sh: 7 cle 1.4	inting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required ade as per manufacturer's specifications to give protective and decorative finish including aning washing of surface etc. complete with: On new work (Two or more coats applied @ 3 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	65.10	Sqm
	8 (1 co	widing and laying damp proof course (upto 50mm thick) with plain cement concrete 1:2:4 ement: 2 coarse sand: 4 graded crushed stone aggregate 20mm nominal size) including work.	0.51	Cum
	9 section	iding stainless steel railing/ grill made of S.S. flats, hollow S.S. pipe or square/ rectangular ons of approved design fixing in stair case, balcony or other places with metal fasteners tainless steel bolts etc complete.SS Grade 204	325.0	Kg
	0 using	ding and laying nominal mix Reinforced cement concrete with crushed stone aggregate concrete mixer in all works upto plinth level excluding cost of form work. 8 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 40mm nominal size).	6.00	Cum
1	be spli 10 mm placing	the post/ strut in cement concrete block.	171.02	Kg
12	cutting,	ng and placing in position reinforcement for R.C.C. work including straightening, bending, binding etc. complete as per drawings including cost of binding wire all e:Thermo-Mechanically treated bars	300.05	KG
	position	rk welded in built up sections/ framed work including cutting, hoisting, fixing in and applying a priming coat of red oxide zinc chromate primer. In gratings, frames, ladder, railings, brackets, gates and similar works.	96.752	Kg
4 1	bracing et	g and fixing formwork including centering, shuttering, strutting, staging, propping c. complete and including its removal at all levels, for: Foundations, footings, base of and plinth beam in any shape and size.	34.00 so	qm

S.N.	PARTICULERS OF ITEMS	Quantity	UOM
15	Providing and fixing in position chain linked steel wire fabric made of 4 mm dia G.I. wire of required width in mesh to concrete/ wooden/ angle iron posts including securing and screwing with 2mm dia G.I. wire, G.I. staples, G.I.U-nails or steel pins etc., complete. Aperture 50x50mm	51.00	sqm

कार्यपालन अभियन्ता नगर पालिक निगम, भिलाई सहायक अभियन्ता नगर पालिक निगम, मिलाई

सर्प अभियन्ता नगर पालिक निराम, मिलाई