

MUNICIPAL CORPORATION OF BHILAI

NIT

वार्ड क्र. 28 छावनी राजीव नगर में शिव मंदिर के समीप पक्का शेड निर्माण कार्य।

(As Per PWD Building/Road SOR 01.01.2015 & Electric SOR 01.06.2020)

S.N.	PARTICULERS OF ITEMS	Quantity	UOM
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area),	16.88	Cum
2	including dressing and leveling of pits. In all types of soils. Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete	2.25	Cum
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm normal size). Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using	4.490	Cum
	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size). Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:Thermo-	449.00	Kg
4 	Mechanically treated bars Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including	10.14	Cum
6	dressing etc. complete. Steel work in tubular (round, square or rectangular hollow tubes etc.) structure in built-up sections, Steel work in tubular (round, square or rectangular hollow tubes etc.) structure in built-up sections, trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting, hoisting, fixing in position upto a height of 5m above plinth trusses and frame work including cutting and fixing including cutting and fixing fixing including cutting and fixing fixing fixing fixing fixing fixing fixing fixing fixing	1866.25	Kg
7	Supply and fixing of polymer precoated galvalume profile sheets (17 GE) of approval profile sheets (17 GE) of approval profile approval profile sheets (17 GE) of approval profile approval profile sheets (17 GE) of approval profile approval prof	200.00	Sqm
8	cutting to size and shape wherever required. Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse shades and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed	11.90	Sqm
9	with matching pigment complete. Size above 200x300mm Providing and laying ceramic glazed floor tiles conforming to IS: 15622 of approved size, make, colour, Providing and laying ceramic glazed floor tiles conforming to IS: 15622 of approved size, make, colour, Providing and laying ceramic glazed floor tiles conforming to IS: 15622 of approved size, make, colour,	6.00	Sqm
10	with white cement mixed with matching pigment etc., complete. Size 300x300mm Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface	52.00	Sqm
11	smooth and even. Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior	52.00	Sqm
12	primer applied @ 2.20 kg/ 10 sqm) Providing and laying cement concrete for plain concrete/ reinforced concrete i/c form work, shuttering complete in as per drawings and specifications. (For Village roads)	21.60	Cum
	P.C.C. M-25 Add Extra For Electrification & Sanitation Work	28380.00	LS

Executive Engineer

Municiapal Corporation

Bhilai

Assistant Engineer
Municipal Corporation
Bhilai

Sub Engineer

Municipal Corporation

Bhilai