## NAGAR NIGAM BHILAI

## N.I.T.

वार्ड क्रमांक 16 कुरूद में सार्वजनिक महिला सामुदायिक भवन में छत्तयुक्त हॉल निर्माण कार्य।  AS PER PWD BUILDING S.O.R 01.01.2015					
.NO	PARTICULAR	QTY	UNIT		
1	Excavation for all types and sizes of foundations, trenches and drains or forupto 50m				
	(at least 5m away from the excavated area), including dressing and leveling of pits. In all				
	types of soil				
		13.82	cum		
2					
	Providing and laying nominal mix cement concrete with crushed stone aggregate using				
	concrete mixer in foundation, plinth and at ground level excluding cost of form work.				
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).				
		6.03	cum		
3	Providing and laying nominal mix reinforcement cement concrete with crushed stone				
	aggregate using concrete mixer in all works upto floor five level excluding cost of				
	reinforcement and form work.1:11/2:3 (1 cement : 11/2 coarse sand : 3 graded stone				
	aggregate 20mm nominal size).	15.08	cum		
4	Providing and placing in position reinforcement for R.C.C. work including straightening,				
7					
	cutting, bending, binding etc. complete as per drawings including cost of binding wire in				
	foundation and plinth all complete: Thermo-Mechanically treated bars FE 415				
		1508.00	kg		
5	Providing and fixing formwork including centering, shuttering, strutting, staging, propping				
	bracing etc. complete and including its removal at all levels, for:				
5.a	Foundations, footings, base of columns and plinth beam in any shape and size.				
	, , , , , , , , , , , , , , , , , , , ,	20.88	sqm		
5.b	Columns, Pillars, Piers and likes- rectangular or square in shape				
		40.80	sqm		
5.c	Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in				
	situ)	66.37	cam		
	a 1.10 C	00.57	sqm		
5.c	Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in				
	situ)	17.92	sqm		
6	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002				
0	of class designation 4.0 in foundation and plinth in:	-			
	Cement Mortar 1:6 (1 Cement : 6 Coarse Sand)				
		4.20	cum		
7	super structureBrick work with modular fly-ash lime bricks (FaLG Bricks) confirming to				
	IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1				
	Cement : 6 Coarse Sand)				
		13.28	cum		
8	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in				
	layers not exceeding 20cm in depth consolidating each deposited layer by ramming and				
	watering, including dressing etc. complete.	20.04			
		20.94	cum		

the property and			
9	Providing and laying damp proof course (upto 50mm thick) with plain cement concrete		3
	1:2:4 (1 coment : 2 coarse sand : 4 graded crushed stone aggregate 20mm nominal size)		
TAN M TAN SAN PAR SAN	including formwork		
		0.26	sqm
10	Providing and fixing steel door with M.S. sheet 1mm thick, frame of angle iron, diagonal		
	braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and		
	corners, all necessary fittings complete including applying a priming coat of red oxide zinc		
	chromate primer	140.40	lva
		149.40	kg
11	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round		
	bars welded to steel frame of windows etc. including applying a priming coat of red oxide		
	zinc chromate primer	42.20	ka
		43.20	kg
12	6 mm thick cement plaster of mix:	ı	
	In Cement Mortar 1:4 (1 cement : 4 fine sand)	40.60	aam
		48.60	sqm
13	12mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)	476.00	
• •		156.00	sqm
14	15mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)	105 (0	
	Description and to the citation of the citatio	197.60	sqm
15	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm		
	with water absorption less than 0.5% and onforming to IS: 15622 of approved make, laid		
	on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints		
	with white cement and matching pigments etc. complete.	41.40	eam
16	Distempering with acrylic washable distemper to give an even shade: on new work.(two or	41.40	sqm
	more coats)		
	Initial Coats)	204.60	sqm
17	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as	204.00	Sqiii
17	per manufacturer's specifications to give protective and decorative finish including		
	cleaning washing of surface etc. complete with:		
	On new work (Two or more coats )		
	Off flew work (1 wo of filore coats)	197.60	sqm
18	Painting on new work (two or more coats) to give an even shade with.Premium synthetic	27,100	34111
18	anting on new work (two or more could) to give an even shade when remain symmetre	,	
	enamel paint (2nd top most approved branded quality) to give an even shade.	2	
	Chainer paint (2nd top most approved oranges quanty) to 8.10 mm system	21.36	sqm
			77

ASSTT.ENGINEER

Nagar Palik Nigam, Bhilai

SUB ENGINEER

Nagar Palik Nigam, Bhilai