10

NAGAR	NIGAM	BHILAI
--------------	-------	--------

NIT

वार्ड क्रमांक 19 शास्त्री नगर केम्प 01 में सार्वजनिक सामुदायिक भवन मरम्मत कार्य।

	100		
S.NO	PARTICULAR AS PER PWD BUILDING S.O.R 01.01.2015	QTY	UNIT
5	THETEOLAR	4	
1	Dismontline II		
1	Dismantling flag stone flooring laid in cement/lime mortar including stacking of serviceable		
	material and disposal of unserviceable material within 50 metre lead.	160.00	sqm
2	6 mm thick cement plaster of mix:		
	In Cement Mortar 1:4 (1 cement : 4 fine sand)	160.00	sqm
		1	
3	12mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)	156.00	sqm
4	15mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)	166.40	sqm
5	Distempering with acrylic washable distemper to give an even shade: on new work.(two or		
m	more coats)	316.00	sqm
		Dieter	•
6	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as per		
	Painting new exterior surface (two or more coats) with FREMICAL Painting new exterior surface (two or more coats) with FREMICA		
	washing of surface etc. complete with:		
	On new work (Two or more coats)	166.40	sqm
	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone		
7	Cement concrete flooring with cement concrete 1.2.1 (Communication of the Communication of th		
	aggregate 20min) finished with a result	160.00	sqm
		100.00	Sqin
	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as per		
8	Painting new exterior surface (two or more coals) with TKEMTER TENTER TO Painting new exterior surface (two or more coals) with TKEMTER TO PAINTING TO		
	washing of surface etc. complete with:		
	On new work (Two or more coats)	155.40	
		166.40	sqm
	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to		
9	Brick work with modular fly-ash lime bricks (Fallo Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1		
	IS:12894-2002 of class designation 4.0 in foundation and p		
	cement : 6 coarse sand)	5.12	cum
	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with		
10	Providing and laying vitrified floor tiles with soluble sait printing, or size of sale		
	water absorption less than 0.5% and conforming to 15. 15022 of appropriate with white		
- 1	thick cement mortar 1:4 (I cement : 4 coarse said) including growing		
	cement and matching pigments etc. complete.	46.40	cum

J 57

ASSTT.ENGINEER

Nagar Palik Nigam, Bhilai

SUB ENGINEER

Nagar Palik Nigam, Bhilai