

# OFFICE OF THE NAGAR NIGAM BHILAI ZONE NO-05.


## DIST-DURG


ESTIMATE NAME : - OFFICE BUILDING JD OFFICE DURG-DIVISION


AT WARD No.-64 SECTOR-10

ESTIMATE HAS BEEN PREPARED AS PER SOR PWD (B&R) W.E.F. 01/01/2015

S.No.	ITEM	QTY	PER
1	3	8	10
1	Brick work with modular fly-ash lime bricks (FALG Bricks) confirming to IS:12894-2002 of class designation 40 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	69.004	cum
2	6mm thick cement plaster of mix: In Cement mortar 1:3 (1 cement : 3 fine sand)	247.08	sqm
3	12mm thick cement plaster of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand)	458.42	sqm
4	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand)	156.62	sqm
6	Providing and laying ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.	354.84	sqm
7	Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and even. 12 mm plaster area 06 MM PLASTERED AREA	705.5	sqm
8	Finishing walls with water proofing cement paint to give an even shade. On new work (Two or more coats)	615.04	sqm
9	Painting on new work (two or more coats) to give an even shade with: SATIN SYNTHETIC ENAMEL PAINT	55	sqm
10	Painting exterior surface with TEXTURED exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats)	615.04	sqm
11	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer.	1200	kg
12	Providing and fixing steel door made of angle iron of suitable sizes with M.S. grill of approved pattern made of M.S. flats or square or round bars coat of red oxide zinc chromate primer.	115	KG

  
EXECUTIVE ENGINEER  
MUNICIPAL CORPORATION  
BHILAI

  
ASSISTANT ENGINEER  
MUNICIPAL CORPORATION  
BHILAI

  
SUB ENGINEER  
MUNICIPAL CORPORATION  
BHILAI