

MUNICIPAL CORPORATION BHILAI


NIT

वार्ड क्र. 36 गौतम नगर आश्रम सामुदायिक भवन का विस्तारीकरण कार्य।

(AS PER PWD BUILDING SOR 01-01-2015 & ELECTRICAL SOR 01.06.2020)

SN	DETAILS OF ITEM	QTY.
1.	Demolishing brick masonry including arches, stacking of serviceable material disposal of unserviceable material within 50 metres lead. In cement mortar. @Rs. 263.00/m ³	0.84 m ³
2.	Demolishing brick masonry including arches, stacking of serviceable material disposal of unserviceable material within 50 metres lead. In cement mortar. @Rs. 768.00/m ³	0.45 m ³
3.	Excavation for all types and size of foundation, trenches and drains or for any other purpose ---- lift and lead upto 50m including dressing and leveling of pits.	36.22 m ³
4.	Providing and laying mechanically mixed cement concrete with crushed stone aggregate excluding cost of centering and shuttering 1:4:8	9.22 m ³
5.	Providing and filling in plinth with sand/Crusher dust and hard moorum under floor, including ----- cost of all labour, materials, T & P etc. complete required for the work.	10.00 m ³
6.	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work. 1:1 ½ :3	25.67 m ³
7.	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, ----- including cost of binding wire all complete. Thermo-Mechanically treated bars.	2181.95 Kg.
8.	Brick work with modular fly-ash lime bricks (FALG Bricks) confirming to IS:12894-2002 of class designation 40 in foundation and plinth in :Cement Mortar 1:6	2.74 m ³
9.	Brick work with modubr fly-ash lime bricks (FALG Bricks) confirming to IS:12894-2002 of class designation 40 Cement Mortar 1:6 Extra for brick work in superstructure: Above plinth and upto floor five level	15.33 m ³
10.	Providing and fixing formwork i/c centering, shuttering, strutting, staging, propping bracing etc. --, footings; base of columns and plinth beam in any shape and size	18.48 m ²
11.	Providing and fixing of formwork including centering, shuttering, strutting, staging, propping, bracings etc. --- plinth level.Columns- rectangular or square in shape	54.00 m ²
12.	Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)	60.64 m ²
13.	Steel work welded in built-up section trusses and framed work i/c cutting, hoisting, fixing in position and applying a priming coat of red lead paint.	333.96 Kg
14.	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer.	246.00 Kg
15.	Providing & Laying damp proof course (up to 50mm thick) with plain cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded crushed stone aggregate 20mm nominal size) including formwork.	0.270 m ²
16.	6mm thick cement plaster a) In Cement mortar 1:3	60.64 m ²
17.	12mm thick cement plaster for cm 1:5 i/c neat cement punning.	91.36 m ²
18.	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand)	90.36 m ²
19.	White washing with whiting to give an even shade. On new work (Three or more coats)	255.96 m ²
20.	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to IS : 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.	54.50 m ²

21	Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	28.26
22	<u>Rain water harvesting system</u> Providing and constructing soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with well burnt modular clay bricks crushing strength not less than 35kg/cm ² and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design.	1 Each
23	<u>Electrification work</u> As per electrical Sor 01.06.2020	11000.00 Lum-Sum



Executive Engineer
Municipal Corporation
Bhilai

Assistant Engineer
Municipal Corporation
Bhilai



Sub Engineer
Municipal Corporation
Bhilai