15 Hibiscus (Flower)/ Rose

MUNICIPAL CORPORATION OF BHILAI & ONIVI



Each

80.00

वार्ड क्र. 29 मोची मोहल्ला में उद्यान निर्माण कार्य।

S.N.	PARTICULERS OF ITEMS	Quantity	UOM
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.	6.00	Cum
2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement: 4 coarse sand: 8 graded stone aggregate 40mm nominal size).	3.00	Cum
3	and the control and the contro	10.64	Cum
4	nagreeae zonim nonman size Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:	532.00	Kg
\neg	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:	106.40	sqm
5	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.	36.00	Cum
,	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, emping and sweeping etc. complete of minimum compressive strength of 250 kg/sq.cm pigment Coloured (nubber mould) precast interlock concrete blocks	80.00	sqm
1	Surface dressing of the ground including removing vegetation and making up andulations and in-equalities not exceeding 15 cms in depth/ height ncluding disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed area).	900.00	sqm
	Supplying and stacking of good earth at site including royalty, loading, unloading and carriage upto 5 km (earth measured in stacks will be adverd by 20% for navment)	90.00	Cum
i	conced by 2009 to parmissis. usupplying and stacking at site well decayed cow dung manure from approved source, ncluding loading, unloading and carriage upto 5 km (manure measured in stacks will be educed by 8% for payment).	46.00	Cum
9	Spreading of sludge, dump manure or/and good earth in required thickness (Cost of ludge, dump manure or/ and good earth to be paid separately).	12.00	Cum
l	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size).	9.00	Cum
I	Providing and planting following herbs in garden including preparation of soil, base plantation, providing and spreading different fertilizers, soil and sand: Hedges like Alife, Porenta, Tikoma etc	600.00	Each
ı İ	Furn like Arica, China etc (3 year old)	25.00	Each

		Quantity	UOM
S.N	. PARTICULERS OF ITEMS	600.00	sqm
16	Carpet grass (well developed)		
_	Carpet grass (well developed) Grassing with 'Doob' grass including watering and maintenance of the lawn for 30 days	750.00	sqm
17			-4
	and fit for mowing including supplying good earth if needed (the good earth shall be		
	paid for separately). In rows 5 cm apart in either direction. Carrying out the resistivity survey by VES method using Schlumberger configuration for	3	
	llocating the proper spot for drilling of tube well within the selected habitation, including	1	Point
18	Inhotography, interpretation of resistivity data and submission of report in the desired		
	format along with resistivity readings, necessary graph and photographs. (only successful		
	point is payable) Boring/drilling bore well perfectly vertical for the specified depth suitable to receive		
	required dia for casing/ strainer pipe, by suitable method		
	prescribed in IS: 2800 (part I), including collecting samples from different strata,		
19	preparing and submitting strata chart/bore log, including hire & running charges of all		
	equipments, tools, plants & machineries required for the job, all complete as per		
	direction of Engineer-in-charge upto 90 metre depth below ground level.		
	All types of soil 150 mm nominal dia	45.00	Mtr.
-	Rocky strata including Boulders. 150 mm nominal dia	1.50	Mtr.
	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket		Mtr.
- 1	as per IS: 1239 (Part-1&Part-2) 1992 with IVth of reputed & approved make,		
	including required hire & labour charges, fittings & accessories, all complete, for all	47.00	
	depths, as per direction of Engineer- in-charge. 150 mm nominal dia		
	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive		
	required dia for casing/ strainer pipe, by suitable method	44.00	Mtr.
	prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and charges of all equipments, tools, plants & machineries required for the		
	ob, all complete as per direction of Engineer-in-charge beyond 90 metre & upto 150		
	netre depth below ground level.		
. I-			
I P	royiding and fixing suitable size threaded mild steel cap or spot welded plate to the top		
2 o	f bore well housing/ casing pipe, removable as per requirement, all complete for bore	1	Each
W	vell of: 150 mm nominal dia	-	
P	rell 0: 150 mm nommar una roviding and laying in trenches G.I. pipes medium class complete with G.I. fittings roluding excavation of trenches, refilling the same and testing of joints complete: 25	150.00	Mtr.
12	nm dia. nominal bore roviding and fixing 15 mm nominal bore C.P. brass fittings of approved make and		
4 c	onforming to IS:8931 including C.P. brass extension if	4	Each
- 1	1 1 0: 1 (_
P	roviding and fixing brass/ gun metal gate valve with C.I. wheel of approved quality		T1
	crewed end):	4	Each
1.			aller transfer of
P	or mm nominal bore roviding and fixing 15 mm nominal bore Brass bib/stop cock of approved quality:	. 4	Each
	ib cock (350 grams)		girai ka
	ainting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of	1	10 EV
P	equired shade as per manufacturer's specifications to give protective and decorative		ment of the
re	nish including cleaning washing of surface etc. complete with:	495.90	Sqm
7 fi	n new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming		
	act of outgries primar applied @ 2.20 kg/10 sqm)	and the second second	de la constantina
TP.	ainting on new work (two or more coats) to give an even shade with:	5.40	Sqm

28 Painting on new work (two or more coats) to give an even shade with:

Satin synthetic enamel paint

S.N.	PARTICULERS OF ITEMS	Quantity	UOM
20 0	Supply Of Swaged steel tubular Pole as per IS 2713 with base plate of size 300 x 3000 x 5000	4	Each
30	Erection of steel tubular pole or rail pole in cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size) foundation including excavation & refilling etc as required of 7 metre to 10 metre	4	Each
31	Supply & fixing water tight terminal box made of 1.6 mm thick M S Sheet with detachable gland plate in bottom 4 way connector & 1 No. SPMCB inside the box for cable connection fixed to pole with 2 Nos. Clamp made from 40 x 3 mm MS flat with 2 Nos. nut bolts dully painted with 2 coat red oxide paint & 2 coat aluminum paint somplets as required 30 x 20 x 15 cms.	4	Each
32	Supply & Making end termination with brass compression gland & aluminum lugs for following size armored aluminum conductor power cable of 1.1 KV grade as required 3 x 25 sq.mm	10	Each
33	Supply & fixing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV grade power cable core/lead pressed with high pressure cramping tool including connection to switch gear/MCCB etc as required 25 sq.mm.	25	Each
34	Supply & Fixing GI Pipe Along With wall or pole/support with 2 nos. MS clamp for protection of underground cable in approved manner including bolts & nuts or metal dash fasteners complete as required 40 mm dia	150.00	Meter
35	Painting new steel & other metallic surface with red oxide zinc chromate primer paint complete with supply of material labour etc including preparation of surface	25.20	Sqm
36	Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as required. Double Over Hang 1.50 metre Long	10	Each
37	Painting wood steel & other metallic surface with aluminum paint complete with material & labour including preparation of surface	25.20	Sqm
38	Providing & Laying Cast In situ Cement Concrete 1:3:6 graded stone aggregate 40 mm nominal size foundation including mixing with mechanical mixer compacting with vibrator finishing & currying etc complete but excluding formwork	1.02	Cum
39	Providing timber steel formwork for cement concrete work at all levels including removing of the same	3.39	Cum
40	without charcoal & salt) as required	4	Set
41	Supplying and drawing following sizes of FR PVC insulated copper conductor, single core cable in the existing surface/ concealed, steel/ PVC conduit/ PVC casing caping as required. 3 x 2.50 sq.mm	72.00	Sqm
4:	Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately). 32 amps	8	Each

		Quantity	UOM
S.N.	Supplying, installation, testing and commissioning of following 230/250 volts LED street light fitting with all accessories like driver, heat sink made of die cast aluminium with IP 66 protection and 5 KV surge protection on pole bracket complete as required	8	Each
44	and furnishing 2 Yrs Guarantee certificate from manufacturer. 40-45 watt Supplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc as required. 2 x 16 sq. mm	150.00	Meter
45 d	NON SOR ITEM Providing & Planting well developed & healthy (5' and above) orna mental plants with fligging holes soil filling & chemical & biological treatment like ficus cycas chhatim, rottle palm, supari palm, musanda & avenue palm, tree including 6th month maintenance ill well established as directed Engineer In charce	40	Each
46 n in	ION SOR ITEM roviding & Planting well established flowering & orna mental plants or shrubs like erium, bougainvillia, crotons, vidhya etc. with digging holes & chemical treatment cluding 6th month maintenance till well established as directed Engineer In charge	70	Each
7 Pr ch est	ON SOR ITEM oviding & Planting well developed succulent healthy orna mental plants with digging emical treatment like thuja, cycas, lolina etc, including 6th month maintenance till well ablished as directed Engineer In charge	20	Each
8 Pro	NN SOR ITEM poiding & fixing of Steel Bench Area 1.20x0.70 m Height 0.45 m above level seating proper grip fixing with 1:2:4 Cement Concrete	10	Each
	DN SOR ITEM oviding & fixing of Double Swing Jhula	1	Each

Executive Engineer
Municiapal Corporation
Bhilai

Assistant Engineer Municipal Corporation Bhilai Sub Engineer Municipal Corporation Bhilai