

MUNICIPAL CORPORATION OF BHILAI



वार्ड 35 सड़क 36 एवं 37 के मध्य स्थित गणेश मैदान का सौंदर्यीकरण कार्य।

As Per PWD Building/Road SOR 01.01.2015, Electrical SOR 01.06.2020 & NON SOR ITEM

S.N	PARTICULERS OF ITEMS	Quantity	UOM
	As Per pwd BUILDING SOR 01.01.2015		
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of oits. In all types of 50i.	13.46	Cum
2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:2-4 (1 cement: 2 coarse sand : 4 graded stone aggregate 40mm nominal size).	5.36	Cum
3	Providing and placing in position angle iron post and strut of required size including bottom to be split and bent at right angle in opposite direction for required length and drilling holes upto 10 mm dia as per requirement including priming coat with red oxide zinc chromate primer and placing the post/ strut in cement concrete block.	352.72	Kg
4	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 14:8:11 cement: 4 coarse sand: 8 graded stone aggregate 40mm nominal size).	5.10	Cum
5	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works up to plint level excluding cost of form work. 11/13/11 Cement: 13/e coarse sand : 3 craded stone agererate 20mm nominal size)	26.64	Cum
6	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:Thermo- Mechanically treated bars	882.00	Kg
7	Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works.	610.96	Kg
	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Foundations, footings, base of columns and plinth beam in any shape and size.	176.40	sqm
9	Providing and fixing in position chain linked steel wire fabric made of 4 mm dia G.I. wire of required width in mesh to concretel wooden/ angle iron posts including securing and screwing with 2mm dia G.I. wire, G.I. staples, G.I.U-nails or steel pins etc., complete. Aperture 50x50mm	105.00	sqm
0	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including fressing etc. complete.	36.00	Cum
1 1	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping and sweeping etc. complete of minimum ompressive strength of 220 kg/sq.cm [imment Coloured rubber mould) precast interlock concrete blocks	80.00	sqm
, 6	urface dressing of the ground including removing vegetation and making up undulations and in- qualities not exceeding 15 cms in depth/ height scluding disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed area).	900.00	sqm
3 k	upplying and stacking of good earth at site including royalty, loading, unloading and carriage upto 5 m (earth measured in stacks will be duced by 20% for paryment).	90.00	Cum

	43	Quantity	UCIN
S.N.	and course including loadings	46.00	Cum
14	fundading and carriage upto 5 km (manure measured in states)	12.00	Cum
15	Spreading of sludge, dump manure or/and good earth in required thickness (Cost of sludge, dump manure or/ and good earth to be paid separately). Providing and planting following herbs in garden including preparation of soil, base plantation,	600	Each
16	sand:		To d
17	Hedges like Alife, Dorenta, Tikoma etc Furn like Arica, China etc (3 year old)	25	Each
18	Hibiscus (Flower)/ Rose	80	Each
19	Carriet grass (well developed)	600.00	sqm
20	Grassing with 'Dooth' grass including watering and maintenance of the lawn for 30 days or more till the grass forms a thick lawn free from weeds and fit for mowing including supplying good earth if needed (the good earth shall be paid for separately). In rows 5 cm apart in either direction.	750.00	sqm
1	Carrying out the resistivity survey by VES method using Schlumberger configuration for locating the proper spot for drilling of tube well within the selected habitation, including photography, interpretation for resistivity data and submission of report in the desired format along with resistivity readings, necessary graph and photographs, (only successful point is payable)	1	Poin
2 1	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for assing/strainer pine, by suitable method prescribed in 1S: 2800 (part 1), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer-in-charge upto 90 metre lepth below ground level.	45.00	Mtr.
3 F	Rocky strata including Boulders. 150 mm nominal dia	1.50	Mtr.
	Jupplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe Platin) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 992 with IVM of reputed & approved make, including required line & labour charges, fittings & ccessories, all complete, for all depths, as per direction of Engineer- in-charge. 150 mm nominal dia	47.00	Mtr.
p	toring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for asing/strainer pipe, by suitable method rescribed in IS: 2000 (part I), including collecting samples from different strata, preparing and harges of all equipments, tools, plants & machineries required for the job, all complete as per direction (Engineer-in-charge beyond 90 metre & upto 150 metre depth below ground level. tocky strata including Roulders. 150 mm nominal dia	44.00	Mtr.
h h	roviding and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well ousing/ casing pipe, removable as per requirement, all complete for bore well of:	1	Each
e	roviding and laying in trenches G.I. pipes medium class complete with G.I. fittings including xcavation of trenches, refilling the same and testing of joints complete: 5 mm dia, nominal bore	150.00	Mtr.
IS re	on John John John John John John John Jo	4	Each
P. 2:	roviding and fixing brass/ gun metal gate valve with C.I. wheel of approved quality (screwed end): 5 mm nominal bore	4	Each
P	royiding and fixing 15 mm nominal bore Brass bib/stop cock of approved quality:	1	

(29)
O OF ITERM

TS.N	PARTICULERS OF ITEMS	Quantity	UOM
31	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer anolied @ 2.20 kc/ 10 sam)	495.90	Sqm
32	Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	5.40	Sqm
	As Per PWD ELECTRICAL SOR 01.06.2020		
33	Supply Of Swaged steel tubular Pole as per IS 2713 with base plate of size 300 x 3000 x 6 mm welded at bottom specified height including painting with one coat of red oxide zinc chromate primer. Designation 410 SP-26 height 9.00 metre	4	Each
34	Erection of steel tubular pole or rail pole in cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size) foundation including excavation & refilling etc as required of 7 metre to 10 metre	4	Each
35	Supply & fixing water tight terminal box made of 1.6 mm thick M S Sheet with detachable gland plate in bottom —. 4 way connector & 1 No. SPMCB inside the box for cable connection fixed to pole with 2 Nos. Clamp made from 40 x 3 mm MS flat with 2 Nos. nut bolts dully painted with 2 coat red oxide paint & 2 coat aluminum paint complete as required 30 x 20 x 15 cms	4	Each
36	Supply & Making end termination with brass compression gland & aluminum lugs for following size armored aluminum conductor power cable of 1.1 KV grade as required 3 x 25 sq. mm	10	Each
37	Supply & Inxing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV grade power cable core/lead pressed with high pressure cramping tool including connection to switch gear/MCCB etc as required 25 so per	15	Each
38	Supply & Fixing GI Pipe Along With wall or pole/support with 2 nos. MS clamp for protection of underground cable in approved manner including bolts & auts or metal dash fasteners complete as required 40 mm dia	200.00	Meter
39	Painting new steel & other metallic surface with red oxide zinc chromate primer paint complete with supply of material labour etc including preparation of surface	23.60	Sqm
40	Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffer of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as required. Double Over Hang 1.50 metre Long	10	Each
	Painting wood steel & other metallic surface with aluminum paint complete with material & labour including preparation of surface	23.60	Sqm
42	Providing & Laying Cast In situ Cement Concrete 1:3:6 graded stone aggregate 40 mm nominal size oundation including mixing with mechanical mixer compacting with vibrator finishing & currying etc omplete but excluding formwork.	1.02	Cum
43 I	Providing timber steel formwork for cement concrete work at all levels including removing of the same	3.39	Cum
a . le	arthing with G.I. earth pipe 4.5 m long 40 mm dia including accessories & providing masonary nelosure with cover plate having locking arrangement watering pipe etc (But without charcoal & salt) required	4	Set
" [upplying and drawing following sizes of FR PVC insulated copper conductor, single core cable in the sisting surface concealed, steel/ PVC conduit/ PVC casing caping as required. 3 x 2.50 sq.mm	80.00	Sqm
32	roviding and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling oles on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).	20	Each
7 su	upplying, installation, testing and commissioning of following 230/250 volts LED street light fitting the all accessories like driver, heat sink made of die cast aluminium with IP 66 protection and 5 KV ges protection on pole bracket complete as required and furnishing 2 Yrs Guarantee certificate from anufacturer, 40-45 watt	8	Each
8 1911	pplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, unninum conductor power cable of 1.1 KV grade direct in ground including excavation, sand shioning, protective covering and refilling the trench et as required.	284.00	Meter

		Quantity	OCM
S.N.	PARTICULERS OF ITEMS		
	As Per PWD Road SOR 01.01.2015	19.200	Sqm
49	Cement art Mural work		
50	NON SOR ITEM Providing & Planting well developed & healthy (5' and above) orna mental plants with digging holes soil filling & chemical & biological treatment like ficus cycas chihatim, bottle palm, supari palm, musanda & avenue palm, tree including 6th month maintenance till well established as directed Engineer In charge	38	Each
51	NON SOR ITEM Providing & Planting well established flowering & orna mental plants or shrubs like nerium, bougainvilla, crotons, vidhya etc. with digging holes & chemical treatment including 6th month maintenance till well established as directed Engineer In charge	75	Each
52	Imministrative transfer as unreced nature. The Mon Son TEM Providing & Planting well developed succulent healthy orna mental plants with digging chemical treatment like thuja, cycas, lolina etc, including 6th month maintenance till well established as directed Engineer in charge	20	Each
53	NON SOR ITEM Providing & fixing of Steel Bench Area 1.20x0.70 m Height 0.45 m above level seating proper grip fixing with 1:2:4 Cement Concrete	10	Each
54	NON SOR ITEM Providing & fixing of Double Swing Jhula	1	Each

Executive Engineer Municiapal Corporation Bhilai Assistant Engineer Municipal Corporation Bhilai Sub Engineer Municipal Corporation Bhilai