MUNICIPAL CORPORATION OF BHILAI

कार्य का नाम —वार्ड 36 कुष्ठ अस्पताल केन्द्र का संघारण कार्य। (डी.एम.एफ.मद)

(As Per PWD Building SOR 01.01.2015 & Electrical SOR 01.06.2020)


| S.N. | PARTICULERS OF ITEMS | Quantity | UOM | Rate |
|-------------|--|----------|-----|---------|
| 1 | Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. | 100.00 | Sqm | 222.00 |
| 2 | Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth levelexcluding cost of form work. 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). | 2.10 | Cum | 4163.00 |
| 3 | Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete: Thermo-Mechanically treated bars | 450.00 | Kg | 54.50 |
| 4 | Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) | 21.00 | Sqm | 235.00 |
| 5 | Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand) | 10.00 | Cum | 3263.00 |
| | Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:3 (1 sement : 3 fine sand) | 21.00 | Sqm | 93.00 |
| | Providing and making 12mm thick cement plaster of mix: In Cement mortar 1:4 (1 ement: 4 fine sand) | 100.00 | Sqm | 103.00 |
| 8 F | Providing and making 15mm thick cement plaster of mix: In Cement mortar 1:5 (1 ement: 5 fine sand) | 100.00 | Sqm | 113.00 |
| 9 5 | Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and 12 mm thick bed of cement Mortar 1:3cement lurry @ 3.3kg per sqm including pointing in white cement mixed with matching igment complete. Size upto 200x300mm | 50.00 | Sqm | 587.00 |
| 0 c | roviding and laying ceramic glazed floor tiles conforming to IS: 15622 of approved ize, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement: 4 oarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Size 300x300mm | 55.00 | Sqm | 692.00 |
| 1 aj | roviding and fixing M.S. grill of approved pattern made of M.S. flats or square or bund bars welded to steel frame of windows etc. including oplying a priming coat welded to frame with all necessary fitting complete including oplying a priming of red oxide zinc chromate primer | 575.00 | Kg | 67.50 |
| Prince 2 at | roviding and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle on, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates junctions and corners, all necessary fittings complete including applying a priming out of red oxide zinc chromate primer. | 410.00 | Kg | 75.00 |

Didd!

| 是一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个 | Quantity | UOM | Pate. |
|--|--|--|--|
| DARTICULERS OF ITEMS | April 19 April 2000 Comment | | |
| Painting exterior surface with PREMIUM ACRYLIC SMOOTH and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specifications to give protective and decorative required shade as per manufacturer's specification and decorative required required shade as per manufacturer's specification required required required required required required | 300.00 | Sqm | 74.50 |
| primer applied @ 2.20 kg 10 sq. 10 sq | 300.00 | Sqm | 38.00 |
| (Two or more coats) (Two or more coats) to give an even shade with: Satin synthetic | 47.03 | Sqm | 55.00 |
| enamel paint | 300.00 | Cum | 93.50 |
| Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to giveprotective and decorative required shade as per manufacturer's specifications to giveprotective and decorative finish including cleaning washing of surface etc. complete with:On old work (One or | 60.00 | Sqm | 47.50 |
| Providing and fixing 10 litre capacity P.V.C. low level flushing cistern conforming to IS: 7231, with all fittings and fixtures complete. | 2.00 | Each | 729.00 |
| Painting on old work (two or more coats) to give an even shade with: Satin synthetic | 5.78 | Sqm | 35.00 |
| Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. | 2.00 | Each | 68.50 |
| ast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) conforming to IS: 7231, with flush bend and other fittings and fixtures complete acluding cutting and making good the walls and floors wherever required: | 2.00 | Each | 2899.00 |
| ame colour), conforming to IS: 7231, with all fittings and fixtures complete cluding cutting and making good the walls and floors wherever required: | 2.00 | Each | 2882.00 |
| e walls wherever required: hite Size 550x450 mm | 3.00 | Each | 1430.00 |
| beguerred assessment long x 20mm dia) | 200 | | |
| leaning of joint etc complete on 20 mm thick bed of cement mortar 1:4 (1 cement :4 ordinary cement without any pigment | 2.25 | Sqm | 338.00 514.00 |
| Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, havingthermal fittings i/c fixing the pipe with | 40.00 | m | 133.00 |
| | finish including complete @ 1.43 ltr/ 10 sqm over and including primer applied @ 2.20 kg/ 10 sqm) Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats) Painting on new work (two or more coats) to give an even shade with: Satin synthetic Painting on new work (two or more coats) to give an even shade with: Satin synthetic Painting on new work (two or more coats) to give an even shade with: Satin synthetic renamel paint Providing and applying plaster of paris putty over plastered wall surface including Providing completeMore than 2 mm thickness to make surface even and smooth in scaffolding completeMore than 2 mm thickness to make surface even and smooth in true plumb and line and level. Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to giveprotective and decorative required shade as per manufacturer's specifications to giveprotective and decorative required shade as per manufacturer's specifications to giveprotective and decorative required shade as per manufacturer's specifications to giveprotective and decorative required shade as policy and fixing 10 litre capacity P.V.C. low level flushing cistern conforming to IS: 7231, with all fittings and fixing flush fittings and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. 2 mm dia roviding and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. 2 mm dia roviding and fixing water closet squatting pan (Indian type W.C. pan), 100mm sand ast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) complete conduing cutting and making good the walls and floors wherever required: 2 hite Orissa pattern W.C. pan of size 580x440 mm Providing and fixing vitreous china water closet (European type W.C. pan) with hite ISI marked plastic seat and lid, 10 litre low l | PARTICULERS OF ITEMS Palnting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two finish including cleaning washing of surface etc. complete with: On new work or work (10 squ) and including priming coat of exterior or more coats applied @ 2.20 kg/10 sqm) Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats) Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats) Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint Providing and applying plaster of paris putty over plastered wall surface including Providing and applying plaster of paris putty over plastered wall surface including Providing and applying plaster of paris putty over plastered wall surface including Providing and applying plaster of paris putty over plastered wall surface including Providing and applying plaster of paris putty over plastered wall surface including Providing and applying plaster of paris putty over plastered wall surface including Providing and fixe surface with PREMIUM ACRYLIC SMCOTH exterior paint of required shade as per manufacturer's specifications to giveprotective and decorative finish including cleaning washing of surface etc. complete with:On old work (One or more coats applied @ 0.83 ltr/ 10 sqm) Providing and fixing 10 litre capacity P.V.C. low level flushing cistern conforming to IS: 7231, with all fittings and fixing resulting particles. 2.00 | Panting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two remore coats applied @ 1.20 kg/ 10 sqm) Distempering with acrylic washable distemper to give an even shade. On new work Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats) Distempering with acrylic washable distemper to give an even shade with: Satin synthetic Panting on new work (two or more coats) to give an even shade with: Satin synthetic Panting on providing and applying plaster of paris putty over plastered wall surface including Panting on providing and graphic (a) 0.81 liv 10 sqm) Providing and fixing 10 litre capacity P.V.C. low level flushing cistern conforming to 18: 7.21, with all fittings and fixtures complete. Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on old work (two or more coats) to give an even shade with: Satin synthetic Panting on the coats of coats of the coats of the co |




| .N. | PARTICULERS OF ITEMS | Quantity | UOM | Rate |
|-----|---|----------|-------------|----------|
| | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, havingthermal stability for hot & cold water supply including all CPVC plain &brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge.25 mm nominal outer dia .Pipes. | 20.00 | m | 213.00 |
| 28 | Providing and placing on terrace (at all levels) polyethylene water storage tank ISI marked with cover and suitable locking arrangement and holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. | 1000.00 | Ltr | 7.30 |
| 29 | Providing and laying in trenches G.I. pipes medium class complete with G.I. fittings including excavation of trenches, refilling the same and testing of joints complete:25 mm dia. nominal bore | 15.00 | Mt | 222.00 |
| 30 | Providing and laying in trenches G.I. pipes medium class complete with G.I. fittings including excavation of trenches, refilling the same and testing of joints complete:15 | 15.00 | Mt | 131.00 |
| 31 | Providing and fixing on wall surface G.I. pipes medium class complete with G.I. fittings and clamps, including cutting, making good the walls etc. and testing of joints complete: 25 mm dia. nominal bore | 1.00 | Mt | 258.00 |
| 32 | Providing and fixing gun metal gate valve with C.I. wheel of approved quality | 1.00 | No | 436.00 |
| 33 | (screwed end): 25 mm nominal bore Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved quality: Bib cock (250 grams) | 10.00 | No | 185.00 |
| 34 | Electrification Work As electric SOR 01.06.2020 Lum-Sum | 1.00 | Lum_s um | 20000.00 |
| 35 | Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soil | 7.166 | Cum | 185.00 |
| 36 | Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor | 0.3 | Cum | 371.00 |
| 37 | Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size). | 0.0747 | Cum | 2659.00 |
| 38 | Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in:Cement Mortar 1:6 (1 cement : 6 coarse sand) | 0.6 | Cum | 3263.00 |
| 39 | Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in:Cement Mortar 1:6 (1 | 3 | Cum | 3384.00 |
| 4 | Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size). | 2.695 | Cum | 4163.00 |



| | | Quantity | UOM | Rate |
|----------|---|----------|-----|----------|
| gentres. | PARTICULERS OF ITEMS | | | a second |
| S.N | Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete: Thermo-including cost of binding wire in foundation and plinth all complete: Thermo-including cost of binding wire in foundation and plinth all complete. | 2.6952 | Kg | 54.50 |
| 42 | Mechanically treated bars FE 415 Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: propping bracing, base of columns and plinth beam in any shape and size. | 5.82 | sqm | 139.00 |
| 43 | Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:Columns, Pillars, Piers and likes- rectangular or square in shape | 6.08 | sqm | 297.00 |
| 44 | Providing and laying damp proof course (upto 50mm thick) with plain cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded crushed stone aggregate 20mm nominal size) including form work. | 0.50 | Cum | 4237.00 |
| | Providing and making 12mm thick cement plaster of mix:In Cement Mortar 1:6 (1 | 32.28 | Sqm | 91.50 |
| 45 | cement: 6 fine sand) Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works. | 84.00 | Kg | 68.00 |
| | 1 - i - 1 terreport unto 5 km lead Earth | 7.17 | Cum | 111.00 |
| 48 | Carriage by mechanical transport upto 5 km lead:Earth Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with:On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)As Per 12mm Plaster | 32.28 | Sqm | 74.50 |
| 19 | Painting on new work (two or more coats) to give an even shade with: | 15.00 | Sqm | 55.00 |
| 0 1 | Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at east 5m away from the excavated area), including dressing and leveling of pits. In all types of soil | 6.75 | Cum | 185.00 |
| , e | Providing and laying nominal mix plain cement concrete with crushed stone ggregate using concrete mixer in all works upto plinth level xcluding cost of form work. 2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size). | 0.68 | Cum | 3552.00 |
| 2 | Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Columns, beams & walls- circular or any other geometrical shape other than square and rectangular in all sizes | 7.68 | sqm | 356.00 |

Die Sie

| s.N. | PARTICULERS OF ITEMS | TO PERFORM PROPERTY. | NY THE BUILDING | Aller State of the |
|------|---|----------------------|-----------------|--|
| | Providing and laying nominal minutes | Quantity | UOM | Rate |
| 53 | work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size) | 1.47 | Cum | 4163.00 |
| | Providing and placing in position reinforcement 6. 7. 7. | | | |
| 54 | including cost of binding wire in foundation and plinth all complete: Thermo-Mechanically treated bars FE 415 | 146.8 | Kg | 54.50 |
| 55 | Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer. In stringers, treads, landings etc. of stair cases including use of chequered plate wherever required, all complete. | 107.77 | Kg | 68.00 |
| 56 | Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. | 4.61 | Cum | 371.00 |
| 57 | Providing and making 12mm thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand) | 5.52 | sqm | 103.00 |
| 58 | Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm) | 5.52 | sqm | 74.50 |
| 59 | Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint | 5.10 | sqm | 55.00 |
| 60 | Surface dressing of the ground including removing vegetation and making up undulations and in-equalities not exceeding 15 cms in depth/ height including disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed area). | 50 | Sqm | 7.20 |
| 61 | Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soil | | Cum | 185.00 |
| 62 | Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size). | 0.8 | Cum | 2659.00 |
| 63 | Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). | 0.8 | Cum | 4073.00 |
| 64 | Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. | 5.00 | Cum | 371.00 |



| | PARTICULERS OF ITEMS | Quantity | UOM | Rate |
|----|--|----------|-----|--------|
| 65 | Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping and sweeping etc. complete of minimum compressive strength of 250 kg/sq.cm Pigment Coloured (rubber mould) precast interlock concrete blocks | 52.00 | sqm | 632.00 |

कार्यपालन अभियन्ता नगर पालिक निगम, मिलाई

नगर पालिक निगम, मिलाई नगर पालिक निगम, मिलाई