MUNICIPAL CORPORATION BHILAI (C.G.)

NIT

Name of work :- वार्ड कं.70 (पुराना वार्ड कं. 70) हुडको L.I.G 86 के पीछे स्थित बस्ती में बोर खनन एवं पाईप लाईन विस्तारीकरण कार्य।

	Description and details of work		
1	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by itable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer–in-charge upto 90 metre depth below ground level. All types of soil	Qty.	Unit
	150MM DIA	20	Rmt
2	Rocky strata including Boulder		
	150MM DIA	22	Rmt
3	Supplying, assembling, lowering and fixing in vertical position bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all depths, as per direction of Engineer- in-charge, 150mm nominal size dia	20.00	Rmt
4	maximum rate of usable water yield without sand content (beyond permissible limit), with required capacity air compressor, running the compressor for required time till well is fully		
5	Providing and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well housing/ casing pipe, removable as per requirement, all complete for bore well of: 150mm nominal size dia	1.00	each
6	Providing and fixing on wall surface G.I. pipes medium class complete with G.I. fittings and clamps, including cutting, making good the walls etc. and testing of joints complete:		
:	25 mm dia. nominal bore	55.00	Rmt
	50 mm dia. nominal bore	51.00	Rmt
	Description 101 Maria 1 and 1		
7	Providing ISI Mark 32 mm dia G.I. (B class) riser pipe and M. plunger rod in 3 meter length socketed on one end as per IS: 1239 (Part I) 1990 with up to date amendments and socket as per IS: 2062/1990 up to date amendment	21.00	Rmt
	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.(In all types of soils.) below GB	35.00	cum
9	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work	0.32	cum
-	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS 12894-2002 of class designation 4.0 in foundation and plinth in 7.5.4 Cement Mortar 1:6 (1 cement: 6 coarse sand) Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked with cover and switch half like the provided with sover and switch half like the provided with switch half like the provided with the provided with switch half like the provided with the provide	2.24	
1	ISI: 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank		ltr
	Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved quality:		

	19.12 Providing and fixing G.I. Union in existing G.I. pipe line, cutting and threading the		6
13	pipe and making long screws including excavation, refilling the earth or cutting of wan		
	and making good the same complete wherever required :	2.00	each
a	19.12.2 20 mm nominal bore.	2.00	each
b	19.12.3 25 mm nominal bore. 19.14 Providing and fixing 15 mm nominal bore C.P. brass fittings of approved make		*
14	and conforming to IS:8931 including C.P. brass extension if required:		
	19.14.6 Stop cock (concealed) (600 grams)	2.00	each
a	to the fall of approved make/duality,	3.00	each
b 15	3.1 Providing and laying nominal mix plain cement concrete values of form aggregate using concrete mixer in all works upto plinth lever excluding cost of form		
	work. 3.1.5 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal	0.10	cum
a	size).		
16	12.3 Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 12.3.1 40 mm thick	6.00	sqm
17	Supplying, installation, testing and commissioning of submersible pump sectors supply system with submersible motor directly coupled to multi-stage submersible pump of specified discharge capacity, head, delivery size in existing bore well including 2 sets of suitable size holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible cable of standard length etc. as required.1.5.0	1.00	Each
18	Supply, installation, testing and commissioning of 1-5 in 1 phase stand 1.6 mm thick starter cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following panel mounting switchgears there in including connection inter-connection etc. as required. a) Phase indicating lamps with fuses and toggle switches 1 set b) 1/2/3 HP 1 phase DOL starter with over load and no volt relay 1 No c) 25 A "C" curve DPMCB 1 No d) Voltmeter 0-250 V 1 set	1.00	Each
19	e) Ammeter 0-10 A 1 set Supplying and laying following sizes one number PVC insulated/XLPE, PVC sheathed steel armoured, aluminium conductor power cable of 1.1 KV grade direct in groun including excavation, sand cushioning, protective covering and refilling the trench et as required.	76.00	Metre

EXECUTIVE ENGINEER
MUNICIPAL CORPORATION
BHILAI

ASSISTANT ENGINEER
MUNICIPAL CORPORATION
BHILAI

SUB ENGINEER
MUNICIPAL CORPORATION
BHILAI