

## MUNICIPAL CORPORATION BHILAI


### NIT


कार्य का नाम :- कुसुम कानन नर्सरी एवं मधुकाभिनी उद्यान का मरम्मत एवं रंगारोगन कार्य।

S.N.	Particulars	Unit	Qty.	Rate	Amount
1	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.				
	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	Cum	2.00		
2	Floor painting with superior quality enamel paint to give an even shade.				
	On old work (one or more coats)	Sqm	800.00		
3	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with:				
	On old work (One or more coats applied @ 0.83 ltr/ 10 sqm)	Sqm	1200.00		
4	Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer.				
	65 x 65 x 6 mm	Kg			
	50 x 50 x 5 mm (Trass)	Kg	525.19		
5	Providing corrugated G.I. sheet roofing including vertical/ curved surfaces fixed with galvanized iron, J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead including painting with primer and paint on overlapping of sheets complete excluding the cost of purlins rafters and trusses. (Zinc coating not less than 272 gms/sqm)				
	0.63 mm thick sheet (weight 5.70 kg/m2)	Sqm	130.68		

*[Handwritten Signature]*

6	Brick work with modular well burnt (open bhatta) clay bricks of crushing strength not less than 20 kg/sqcm and water absorption not more than 25% in foundation and plinth in:				
	Cement Mortar 1:6 (1 Cement : 6 Coarse Sand)	Cum	12.80		
7	Providing ridges or hips of 60cm overall width in plain G.I. sheet fixed with galvanized washers J or L hooks, bolts and nuts 8mm G.I. limpet and bitumen washers complete.				
	0.80 mm thick sheet with zinc coating not less than 275 gm/sqm	Mtr	11.00		
8	Providing and fixing 15 cm. wide 45cm. overall semi circular plain G.I. sheet gutter with iron brackets 40x3 mm size, bolts, nuts and washers etc. including making necessary connections with rain water pipe complete as per designs.				
	Extra for providing and fixing wind ties of 40x6mm flat iron section.	Mtr	66.00		

  
 कार्यपालन अभियंता  
 नगर पालिक निगम  
 भिलाई

  
 सहायक अभियंता  
 नगर पालिक निगम  
 भिलाई