

MUNICIPAL CORPORATION BHILAI (C.G.)
NIT

कार्य का नाम :- वार्ड-05 लक्ष्मी नगर, दुर्गापारा के पास आंगनबाड़ी निर्माण कार्य।

Pwd Building Sor 01.01.2015 & Electric Sor 01.06.2020

S.No.	Description and details of work	Qty.	Unit
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soil	34.91	Cum
2	Surface dressing of the ground including removing vegetation and making up undulations and in-equalities not exceeding 15 cms in depth/ height including disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed area).	120.00	Sqm
3	Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.	8.40	Cum
4	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete	48.71	Cum
5	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels,		
(A)	Foundations, footings, base of columns and plinth beam in any shape and size.	67.05	Sqm
(B)	Columns, Pillars, Piers and likes- rectangular or square in shape	41.76	Sqm
(C)	Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)	99.98	Sqm
(D)	Beams, lintels, cantilevers & walls	33.97	Sqm
6	Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).	10.12	Cum
7	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	16.12	Cum
8	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete: Thermo-Mechanically treated bars	2470.30	Kg
9	Brick work with modular fly-ash lime bricks (FALG Bricks) conforming to IS:12894-2002 of class designation 35 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	20.24	Cum
10	Extra for brick work in superstructure:	17.18	Cum
11	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	11.32	Cum
12	Half brick thick (9cm) brick masonry with modular well burnt clay bricks of crushing strength not less than 35 kg/sqcm and water absorption not more than 20% in superstructure above plinth level upto floor five level Cement Mortar 1:4 (1 cement : 4 coarse sand)	22.27	Sqm



S.No.	Description and details of work	Qty.	Unit
13	Extra for providing and placing in position hopping 25x1.60 mm or 2 Nos 6mm dia MS bars reinforcement at every third course of half brick masonry.	22.27	Sqm
14	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frame of windows etc. including applying a priming coat of red oxide zinc chromate primer..	300.00	Kg
15	Providing and fixing double glazed hermetically sealed glazing in aluminium windows, ventilators and partition etc. with 6 mm thick clear float glass both side having 12 mm air gap including providing EPDM gasket, perforated aluminium spacers, desiccants, sealant (Both primary and secondary sealant) etc. complete	9.72	Sqm
16	Providing and fixing flush door shutters, conforming to IS 2202 (Part 1), interior grade, commercial type, core of block board construction with frame of first class hard wood and well matched commercial ply veneering with vertical grains, cross bands and face veneers on both faces of shutters excluding hinges	9.14	Sqm
17	Providing and fixing M.S. bright finished or black enameled Butt hinges IS : 1341 marked with necessary iron screws:	15.00	Nos
18	Providing and fixing M.S. bright finished or black enameled sliding door bolts with bolts, nuts and necessary iron screws	10.00	Nos
19	Providing and fixing M.S. bright finished or black enameled Tower bolts (Barrel type) with necessary iron screws	5.00	Nos
20	Providing and fixing M.S. bright finished or black enameled handles with necessary iron screws	10.00	Nos
21	Providing and fixing MS bright finished single hanging door stopper with necessary MS steel screws complete.	10.00	Nos
22	6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand)	112.46	Sqm
23	12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)	120.08	Sqm
24	Providing and making 15 mm thick cement plaster on rough side of single or half brick wall of mix In Cement Mortar 1:5 (1 cement : 5 fine sand)	213.59	Sqm
25	Providing and making 12mm thick plain cement mortar bands in cement mortar 1:4 (1 cement : 4 fine sand) per cm width:	180.00	Rmt
26	Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.	60.21	Sqm
27	Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.	7.95	Sqm
28	KOTA stone slab 25mm thick in risers and treads of steps, skirtingdado and pillar laid in 12mm (Average) thick cement mortar 1:3 (1 cement : 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete. (single stone is to be used for riser and treads of steps and the width of stone for skirting and dado shall be equal to the height of skirting/ dado up to length of 1.0 M.)	1.80	Sqm
29	Wall painting with acrylic luxury emulsion (plastic) paint (top most approved branded quality) to give an even shade. On new work (two or more coats)	232.54	Sqm
30	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats)	213.59	Sqm

S.No.	Description and details of work	Qty.	Unit
31	Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint (top most approved branded quality)	35.99	Sqm
32	Providing and fixing one side polished 25 mm thick RAJIM SAND STONE shelves fixed in walls in cement mortar 1:3 (1 cement : 3 coarse sand) including finishing complete	7.20	Sqm
33	P/F white vitreous flat-back basin 580x400 mm with 15mm C.P. Brass pillar cock with R.S. or C.I. brackets painted white C.P. Brass chain with rubber plug 32 32mm pvc waste pipe complete including cutting and making good the floors and walls where required. White size 450x325 mm	2.00	Nos.
34	P/F 600x 450 barrel edge mirror of superior class (of approved quality) complete with 6mm thick asbestos sheet ground fixed to wooden cleats with brass screws & washer.	1.00	Nos.
35	Providing and fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS : 13592 (4kg/sqcm) including required couplers, jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion etc complete good the wall wherever required.		
	For 75mm dia pipe	3.00	RMT.
	For 100mm dia pipe	3.00	RMT.
36	Providing and fixing on wall face UV stabilized Unplasticised - PVC moulded fittings/ accessories having 3.2mm wall thickness for Rigid PVC pipes conforming to IS : 13592 (heavy) jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion. Nahani trap 110x75mm	2.00	Nos
37	Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved quality: Bib cock (250 grams)	2.00	Nos.
38	Stop cock (350 grams)	2.00	Nos.
39	Providing and fixing 15 mm nominal bore C.P. brass fittings of approved make and conforming to IS:8931 including C.P. brass extension if required Towel rail (600mm long x 20mm dia)	2.00	Nos
40	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge CONCEALED WORK including cutting chases and making good the walls etc.,	15.00	RMT.
41	20mm nominal outer dia pipe	20.00	RMT.
42	25mm nominal outer dia pipe	10.00	RMT.
43	Providing and fixing stainless steel drain jali of approved make/quality	3.00	Nos
44	Providing and fixing brass/ gun metal gate valve with C.I. wheel of approved quality (screwed end):	1.00	Nos.
45	Providing laying and jointing of glazed stoneware pipe grade "A" with stiff mixture of cement mortar in proportion of 1:1 (1 cement : 1 Sand) including testing of joints and earth excavation, refilling and disposal of surplus earth complete in all respect for:- 100mm dia S.W. pipe	3.00	RMT
46	Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete 150mm thick as per standard design: 100mm dia S.W. pipe	3.00	RMT
47	Providing and fixing square mouth S.W. Gully trap of size 150x100mm 'P' or 'S' type grade "A" complete with C.I. grating brick masonry chamber with locally available best quality bricks and 75 th. R.C.C. precast cover made of M-20 grade Cement conc. As per detailed drawings and direction of Engineer 150 x 100 mm size P type	2.00	Nos.

S.No.	Description and details of work	Qty.	Unit
48	Providing and constructing brick masonry chamber for underground pipe and bends with well burnt modular clay bricks crushing strength not less than 35kg/cm ² in cement mortar 1:4 (1 cement : 4 coarse sand) RCC cover of suitable size and 75mm thick with 1:1.5:3 mix (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) including reinforcement 8mm dia bars at 150mm both ways and MS hooks for lifting, including foundation concrete 1:5:10 (1 cement : 5 fine sand : 10 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete as per standard design Inside dimensions 500x700 mm and 45 cm deep for pipe line with one or two inlets	1.00	Nos
49	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI : 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	500.00	Lit
50	Providing and fixing water closet squatting pan (Indian type W.C. pan), 100mm sand cast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) conforming to IS : 7231, with flush bend and other fittings and fixtures complete including cutting and making good the walls and floors wherever required White Orissa pattern W.C. pan of size 580x440 mm	1.00	Nos
51	Providing and constructing soak pit 1.20x1.20x1.20m filled with brickbats including S.W. drain pipe 100 mm diameter and 1.20 m long complete as per standard design.	2.00	Nos
52	Earthing with G.I. earth pipe 4.56 mtr long 40mm dia including accessories and providing masonry enclosure wth cover plate having locking arrangement and watering pipe etc. with charcoal and salt as required	1.00	Nos
53	Providing and fixing loop earthing 6.0 s.w.g dia G.I. wire in existing surface or recessed conduit along other wires as required	30.00	Rmt
54	Providing and fixing metal clad SP & NJ switch fuse unit (re wirable) 230/250 volts with procelain rewirable fuse including drilling holes on the board connections earthing the body etc. as required (Thimblelling shall be paid seperately)	1.00	Rmt
55	Wiring for circuit wiring 3x2.5 sqm PVC insulated cable of ISI marked in concealed rigid steel conduit of suitable size as required 2 wire.x 2.5 sq mm	20.00	Mtr
56	Supplying and fixing on survice / recess following way 240 volts SP & N MCB distribution board of sheet steel phosphatized and powder painted complete with tinned copper busbar neutral busbar earth bar din bar detachable gland plate including interconnections earthing etc. as required (But without MCB / RCCB/ Isolator)	1.00	Nos
57	Wiring for light/ fan/ exhaust fan / call bell point with 1.5 sqmm FR PVC insulated stranded copper conductor single core cable in concealed steel conduit, with 5 amp piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with same size cable etc as required.		
	Short Point	10.00	Point
	Medium Point	10.00	Point
58	Point wiring for 3 Pin socket outlet point with 1.5 Sqm PVC insulated cable with copper conductor ISI mrked in concealed rigid pipe	4.00	Point
59	Wiring for power plug point with 2x4 sq mm FR PVC insulated stranded copper conductor cable in surface steel conduit along with piano type 16 amp switch and 6 pin 16 amps socket outlet with suitable size M.S. box, phenolic laminated sheet, earthing the switch box and socket outlet with same size cable including painting etc. as required	2.00	Nos