MUNICIPAL CORPORATION BHILAI (C.G.)

eame of work :- वार्ड कं. 64 सेक्टर 10 में जयंती स्टेडियम के समीप शौचालय निर्माण कार्झ।

S/NO.	As per Building SOR 01.01.2015 ELEC SOR	OTY.	UNIT
	PARTICULARS	19 10	
1	Surface dressing of the ground including removing vegetation and making up undulations and inequalities not exceeding 15 cms in depth/ height including disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed area).	56.70	Sqm
2	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.	44.94	Cum
3	Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.	44.94	Cum
4	mixer in foundation, plinth and at ground level excluding cost of form work		- 1 - 1
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	3.82	Cum
5	cement: 2 coarse sand: 4 graded crushed stone aggregate 20mm nominal size) including formwork.	1.91	Cum
6	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.		
	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	8.17	Cum
7	level for every floor or part thereof in addition to rate for foundation and plinth:	11.56	Cum
8	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.	19.20	Cum
9	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:	612.75	Kg
	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:		
	Foundations, footings, base of columns and plinth beam in any shape and size.	67.60	Sqm
	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:	Q ²	,
	Columns, Pillars, Piers and likes- rectangular or square in shape	26.40	Sqm
c	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. omplete and including its removal at all levels, for:		
	Veather shade, chhajja, Cornices and mouldings Pq-16, Code No-2.1.14)	3.84	Sqm
P	roviding and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc.		
	omplete and including its removal at all levels, for: eams, lintels, cantilevers & walls	1	
Pi	roviding and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc.	13.08	Sqm
Sı	spended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)	55.20	Sqm
lde	ick work with modular fly-ash lime bricks (FALG Bricks) confirming to IS:12894-2002 of class signation 40 in foundation and plinth in:		
Ce	ment Mortar 1:6 (1 cement : 6 coarse sand)	7.38	Cum
Bri	ck work with modular fly-ash lime bricks (FALG Bricks) confirming to IS:12894-2002 of class signation 40 in foundation and plinth in:		
Ce	ment Mortar 1:6 (1 cement : 6 coarse sand)	13.95	Cum
Pro	oviding wood work in frames of doors, windows, clerestory windows and other frames wrought med and fixed in position.		

	Sal, bijasal, benteak, khair, haldu	0.12	Cum*
18	of first class hard wood and well matched teak ply veneering with vertical grains or cross bands and		
_	35 mm. thick (single leaf)	13.14	Sam
19	Providing and fixing bright finished brass butt hinges with brass polished MS screws complete:	10.17	Sqm
	100x85x5.50 mm (Heavy Type)	9.00	F
20	Providing and fixing bright finished brass sliding door bolt with nuts and brass polished MS screws 250x16mm	9.00	Each
21		2.00	F
21	Providing and fixing brass door latch with brass polished MS screws complete: 250x16x5 mm	2.00	Each
		2.22	12
22	Providing and fixing bright finished brass tower bolts (barrel type) with brass polished MS screws 200x10mm	2.00	Each
		12.00	
23	Providing and fixing bright finished brass door handles with brass polished MS screws complete: 125 mm	12.00	Each
		2.00	
	Making the opening in brick masonry for door/ window/ clerestory window including dismantling in floor or walls by a still	8.00	Each
24	including dismantling in floor or walls by cutting masonry and making good the damages to walls, flooring and jambs are masonry and making good		
44	the damages to walls, flooring and jambs complete to match existing		
1	surface i/c disposal of malba/ rubbish to the nearest municipal dumping		
	ground.		
	Float glass panes of thickness 5.5 mm	10.11	
25	Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer.	13.14	Sqm
	applying a priming coat of red oxide zinc chromate primer.		
	1 3 3 3 3 3 4 3 5 5 5 5 5 5 5 5 5 5 5 5 5		
I		250.00	kg
20			
	Size 600x600mm		
		48.00	Sqm
J	Providing and fixing ceramic glazed wall tiles conforming to IS: 15622		-1
	I		
	The same and the control of the company of the comp		1
1.	partially with grey content stuffy (a) 3 3kg nor cam including a six .		
	Printe comoni mixeu with malching nigment complete		
	oize above zouxsoumm	-	in the second
28	6mm thick cement plaster of mix:	94.08	Sqm
*	In Cement mortar 1:4 (1 cement : 4 fine sand)		
29	12mm thick cement plaster of mix:	15.00	Sam
1	In Compat Modes 446 (4 4 - 0.5	10.00	Sqm
7.7	In Cement Mortar 1:6 (1 cement : 6 fine sand)	121.10	3.44
		134.40	Sqm
30 1	15mm thick cement plaster on the rough side of single or half brick wall of mix:		
'	The Cernett Mortal 1:6 (1 cement : 6 fine sand)		
31 <i> </i>	Applying one coat of cement primer on wall surface	106.08	Sqm
1	Wall painting with applie luving ampleter () at the	161.40	
	Wall painting with acrylic luxury emulsion (plastic) paint of required shade to give an even shade. On new work (two or more coats)	101,40	Sqm
33 F	Pointing and a second of the coats)		
33	Painting on new work (two or more coats) to give an even shade with	161.40	Sqm
	odani dynanetic enamei paint		
34	Structural steel work in single section including cutting, hoisting, fixing in	15.00	Sqm
	position and applying a priming coat of red oxide zinc chromate primer		Oqiii
		120.00	KG
 #"	ncluding scaffolding complete		200000000000000000000000000000000000000
יון	Upto 2 mm thickness to make surface and	1	
	Providing and fixing one side polished 25 mm thick RAJIM SAND STONE shelves fixed in walls in	15.00	
e P	POHOLOG TO HILL FLICK KA HW CAND CLONE	15.00	Sqm
86 P	ement mortar 1:3 (1 cement : 3 coarse sand)including finishing complete		
6 F	cement mortar 1:3 (1 cement : 3 coarse sand)including finishing complete.		

Ing and fixing in position chain linked steel wire fabric made of 4 I. G.I. wire of required width in mesh to concrete/ wooden/ angle sts including securing and screwing with 2mm dia G.I. wire, G.I. I. G.I.U-nails or steel pins etc., complete. Aperture 50x50mm Ing and fixing mirror of superior glass (of approved quality) and sired shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: I. 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters are and window, clearstory windows etc (Only area of glass panes to assured). I. 4mm thick Ing and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) I. 3mm thick Ing and fixing laminated glass sheet of 8.76mm thickness in sing and fixing laminated glass sheet of some of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building. (Frame to be loved sizes on aluminium frame work on face of building.)	24.00 3.00 2.00 14.00 3.15	SQM SQM SQM
sts including securing and screwing with 2mm dia G.I. wire, G.I. , G.I.U-nails or steel pins etc., complete. Aperture 50x50mm Ing and fixing mirror of superior glass (of approved quality) and sired shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: 1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters are and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick Iting and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) I 3mm thick Iting and fixing laminated glass sheet of 8.76mm thickness in laminium frame work on face of building. (Frame to be lowed sizes on aluminium frame work on face of building. (Frame to be lowed sizes on aluminium frame work on face of building. (Frame to be lowed sizes on aluminium frame work on face of building. (Frame to be lowed sizes on aluminium frame work on face of building. (Frame to be lowed sizes on aluminium frame work on face of building. (Frame to be lowed sizes on aluminium frame work on face of building.)	3.00 2.00 14.00 3.15	SQM SQM
sts including securing and screwing with 2mm dia G.I. wire, G.I. , G.I.U-nails or steel pins etc., complete. Aperture 50x50mm ng and fixing mirror of superior glass (of approved quality) and hired shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: 1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters are and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick ding and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately)	3.00 2.00 14.00 3.15	SQM SQM
Aperture 50x50mm Ing and fixing mirror of superior glass (of approved quality) and sired shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: 1 5mm thick mirror Ing and fixing glass panes in glazed or paneled and glazed shutters are and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick Iting and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick Iding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately)	2.00	SQM
Aperture 50x50mm Ing and fixing mirror of superior glass (of approved quality) and sized shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: 1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters are and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick ding and fixing aluminium composite panels in approved panel sizes, less and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in ding and fixing laminated glass sheet of building. (Frame to be for separately)	2.00	SQM
ing and fixing mirror of superior glass (of approved quality) and sired shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: 1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick ding and fixing aluminium composite panels in approved panel sizes, less and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in loved sizes on aluminium frame work on face of building. (Frame to be for separately	2.00	SQM
aired shape and size with plastic moulded frame of approved and shade with 6 mm thick hard board backing: 1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters rs and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick ding and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately	2.00	SQM
and shade with 6 mm thick hard board backing: 1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters rs and window, clearstory windows etc (Only area of glass panes to asured). 4mm thick ling and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately	14.00 3.15	SQM
1 5mm thick mirror ing and fixing glass panes in glazed or paneled and glazed shutters rs and window, clearstory windows etc (Only area of glass panes to asured). 4mm thick ling and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately	14.00 3.15	SQM
ing and fixing glass panes in glazed or paneled and glazed shutters rs and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick ling and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in ding and fixing laminium frame work on face of building. (Frame to be for separately	14.00 3.15	SQM
rs and window, clearstory windows etc (Only area of glass panes to assured). 4mm thick ling and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) 1 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in ding and fixing laminium frame work on face of building. (Frame to be sor separately	14.00 3.15	SQM
asured). 4mm thick ling and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately	3.15	
4mm thick ling and fixing aluminium composite panels in approved panel sizes, ess and shape on aluminium frame work on face of building. (Frame paid separately) I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in oved sizes on aluminium frame work on face of building. (Frame to be for separately	3.15	
ling and fixing aluminium composite panels in approved panel state of ess and shape on aluminium frame work on face of building. (Frame paid separately) I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in line of sizes on aluminium frame work on face of building. (Frame to be for separately	3.15	
paid separately) I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in diversity on face of building. (Frame to be some sizes on aluminium frame work on face of building. (Frame to be some separately	3.15	
paid separately) I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in lived sizes on aluminium frame work on face of building. (Frame to be for separately		SQM
I 3mm thick ding and fixing laminated glass sheet of 8.76mm thickness in lived sizes on aluminium frame work on face of building. (Frame to be for separately		SQM
ding and fixing laminated glass sheet of 6.70mm thickness to be byed sizes on aluminium frame work on face of building. (Frame to be for separately		SQM
oved sizes on aluminium traffie work of rade or a size including royalty, loading,	10.00	1 40
for separately the steel producting royalty, loading,	10.00	
for separately the steel producting royalty, loading,	10.00	Cum
lying and stacking of good earth at the mount in stacks will be		Ouin
June / Court measured in studies when	L	17
ding and carriage upto 5 km (salas)	10.00	Cum
ced by 20% for paymenty.	10.00	Met.
ading of sludge, dump manure or/ and good earth to be paid		
	12 00	Sqm
	12.00	100
iding and planting following and spreading different fertilizers, soil and	-	
		Cum
Cornel (11455 Woll 44 conclete Willi older)	2.52	
iding and laying nontrina may be all works upto plinth level		10
e aggregate using consiste work 1:11/2:3 (1 cement : 11/2 coarse sand : 0 gradult of same work 1:11/2:3)		
uding cost of form we want		RS 1084
inal Size).		RS 8130
THE PLUMBING FOR FOUNTAIN		
TER SUPPLY ,PLONIDING		2
CTRIFICATION	. ·	
N SOR	4.00	Each
Speed Jet Of Warm Air With Low House	1.00	4 Mg
ematic Cut Off after approx 5-10 seconds Inch		
errial: ABS PLASTIC, White color, 0/207	1	3 . 7
-blo & Sieck III - LIMOI MOIIII - VVIIII	1.00	Eac
Paper Dispenser M-Fold Wall Mount	1.00	
for Residuration and survivi		
intains Hyguine		-
euring environmentally-friendly, realizing manage costs through controlled dispersory	,	
motes hygiene whilst helping manage		
	1.00	Eac
cont 5Rs Coin	1 -	4
need of electricity Width		
am Height 33 cm		
-th 22 cm Weight10 kg Product Capacity		
pui 22 VIII VIII	· \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
extend of the control	radely). Ariding and planting following herbs in garden including preparation of base plantation, providing and spreading different fertilizers, soil and di-Carpet grass (well developed) Ariding and laying nominal mix plain cement concrete with crushed viding and laying nominal mix plain cement concrete with crushed re aggregate using concrete mixer in all works upto plinth level re aggregate using concrete mixer in all works upto plinth level re aggregate using concrete mixer in all works upto plinth level re aggregate using concrete mixer in all works upto plinth level re aggregate using concrete mixer in all works upto plinth level re aggregate 20mm re aggregate 20mm re aggregate using concrete mixer in all works upto plinth level re aggregate 20mm re a	aradely). 12.00

EXECUTIVE ENGINEER
MUNICIPAL CORPORATION
BHILAI

ASSISTANT ENGINEER
MUNICIPAL CORPORATION
BHILAI

SUB ENGINEER MUNICIPAL CORPOR BHILAI