NAGAR PALIK NIGAM BHILAI

NIT

वार्ड क्र.-14 शांतिनगर क्षेत्रांतर्गत विभिन्न स्थानो में नाली निर्माण कार्य।

	410 337		A Company of the
		Q	U
N	PARTICULAR And the standard of the standard o		
	PARTICULAR Excavation for all types and sizes of foundations, trenches and drains or for any other Excavation for all types and sizes of foundations, trenches and drains or for any other Excavation for all types and sizes of foundations, trenches and drains or for any other		
	in a disposal of excavated Still upto 1.5 in int and issues		
	5m away from the excavated area), including dressing and leveling of pits.	273.00	Cum
	0 11	2,011	
_	the same of mix plain cement concrete will clusted stone and c		
	11 montro unto nlinth level excluding cost of form		
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).		C
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone agg. eg)	39.00	Cum
	Providing and fixing form work including centring, shuttering, strutting, staging,		
3	Providing and fixing form work including centuring, shattering, sh		
	Providing and fixing form work including estating, propping bracing etc. complete and including its removal at all levels, for:		
	propping bracing etc. complete and including its remeable. Foundations, footings, base of columns and plinth beam in any shape and size.	858.00	Sqm
4	Providing and laying nominal mix reinforced cement concrete with crushed stone		
	Providing and laying nominal link removed control aggregate using concrete mixer in all works upto plinth level excluding cost of form		
	work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	94.05	Cum
	A C. D. C. C. work including straightening.		
5	Providing and placing in position reinforcement for R.C.C. work including straightening,		
	cutting bending, binding etc. complete as per drawings including out		
	wire in foundation and plinth all complete:		1
\vdash	Thermo-Mechanically treated bars FE 415	5643.00	Kg
\vdash		5045.00	115
-	Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of		
6	in lowers not exceeding 20cm in depth consolidating oder of		
	layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.		-
L	layer by ramining and watering with a road appropriate	39.00	Cui
7	Carriage by mechanical transport for 5 km lead: Earth		
\vdash	to the standard for the		Cu

ASSTT.ENGINEER Nagar Palik Nigam, Bhilai

Nagar Palik Nigam, Bhilai

ue SW.

> EXECUTIVE ENGINEER Nagar Palik Nigam, Bhilai