

NAGAR NIGAM BHILAI

NIT

वार्ड क्र.-14 शांतिनगर दशहरा मैदान स्थित भवन का संधारण कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015

S.NO	PARTICULAR	QTY	UNIT
1	Dismantling flag stone flooring laid in cement/lime mortar including stacking of serviceable material and disposal of unserviceable material within 50 metre lead.	100.00	sqm
2	6 mm thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand)	180.00	sqm
3	12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)	178.20	sqm
4	15mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)	216.00	sqm
5	Distempering with acrylic washable distemper to give an even shade: on new work.(two or more coats)	358.20	sqm
6	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats)	216.00	sqm
7	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 50 mm thick	100.00	sqm
8	Providing and applying plaster of paris putty over plastered wall surface including scaffolding complete Upto 2 mm thickness to make surface even and smooth in line and level.	358.20	sqm
9	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	2.56	cum
10	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping and sweeping etc. complete of minimum compressive strength of 250 kg/sq.cm Pigment Coloured (rubber mould) precast interlock concrete blocks	22.80	cum
11	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars ... welded to frame with all necessary fitting complete including applying a priming of red oxide zinc chromate primer.	300.00	kg

ASSTT.ENGINEER

Nagar Palik Nigam, Bhilai

SUB.ENGINEER

Nagar Palik Nigam, Bhilai