MUNICIPAL CORPORATION BHILAI (C.G.)

NIT

Name of work:- सेक्टर 6 सतनाम भवन के पास 01 नग बोर खनन कार्य।

15		Qty.	Building SOR 01.01.2
Bo str 1 Pr	escription and details of work bring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/rainer pipe, by itable method prescribed in IS: 2800 (part I), including collecting samples from different strata, reparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants a machineries required for the job, all complete as per direction of Engineer-in-charge upto 90 metre lepth below ground level. All types of soil 150MM DIA	18	Rmt
2	Rocky strata including Boulder		
	150MM DIA	80	Rmt
3	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all	19.00	Rmt
4	depths, as per direction of Engineer- in-charge. 150mm nominal size dia Development of tube well in accordance with IS: 2800 (part I) and IS: 11189, to establish maximum rate of usable water yield without sand content (beyond permissible limit), with required capacity air compressor, running the compressor for required time till well is fully Providing and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well housing/ casing pipe, removable as per requirement, all complete for bore well of: 150mm nominal size dia	1.00	each
5	Providing ISI Mark 32 mm dia G.I. (B class) riser pipe and M. plunger rod in 3 meter length socketed on one end as per IS: 1239 (Part I) 1990 with up to date amendments and socket as per IS: 2062/1990 up to date amendment	21.00	Rmt
6	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.(In all types of soils.) below GB	5	cum
7	excluding cost of form work.	0.32	cum
8	12.3.1 40 mm thick	4.00	sqm
9	mm X 6 mm MS flat, connection with suitable submersible cable of standard length etc. as required.1.5.0 HP, single phase	1.00	Each
10	c) 25 A "C" curve DPMCB 1 No d) Voltmeter 0-250 V 1 set e) Ammeter 0-10 A 1 set	1.00	Each
11	Supplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc as required.	30.00	Metre

ASSISTANT ENGINEER
MUNICIPAL CORPORATION
BHILAI

SUB ENGINEER
MUNICIPAL CORPORATION
BHILAI