	NAGAR NIGAM BHILAI		
	NIT		
	वार्ड क्र.—22 कुरूद ट्रेचिंग ग्राउण्ड में गौठान पशु हेतु शेड निर्माण का	र्य ।	
	(AS PER PWD BUILDING S.O.R 01.01.2015)		
.NO	PARTICULAR	QTY	·UNIT
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soils.		
		51.84	Cum
2	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.		
_		5.76	Cum
3	Providing and laying nominal mix einforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
		24.28	Cum
4	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:		
	Thermo-Mechanically treated bars FE 415	100	34,
		2428.00	Kg
5	Structural steel work riveted or bolted or welded in built-up sections, trusses and frames work upto a height of 5m above plinth level, including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer.		
		10137.60	Kg
6	Supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/- 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7		8_
,	upto any pitch in horizontal/vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.		
7	D	660.00	Sqm
. '	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)		
3	Painting on new work (two or more coats) to give an even shade with:	17.60	Sqm
+	Aluminium paint		
1		-	
	\mathfrak{P}	902.41	Sqm
	ASSTT.ENGINEER SUB ENGINEE	4	