



(16)

NAGAR NIGAM BHILAI**NIT**

विधायक निधि अंतर्गत वार्ड क्र.-27 शास्त्री नगर शिव मंदिर डबरा पारा में सार्वजनिक मंच संधारण कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015

| S.NO | PARTICULAR | QTY | UNIT |
|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|------|
| 1 | 6 mm thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand) | 58.48 | sqm |
| 2 | 12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand) | 107.80 | sqm |
| 3 | 15mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand) | 151.20 | sqm |
| 4 | Distempering with acrylic washable distemper to give an even shade: on new work.(two or more coats) | 166.28 | sqm |
| 5 | Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as.. decorative finish including cleaning washing of surface etc. complete with: On old work (One or more coats applied @ 0.83 ltr/ 10 sqm) | 151.20 | sqm |
| 6 | Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 40 mm thick | 58.48 | sqm |
| 7 | Providing and applying plaster of paris putty over plastered wall surface including scaffolding complete Upto 2 mm thickness to make surface even and smooth in line and level. | 166.28 | sqm |
| 8 | Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars ... welded to frame with all necessary fitting complete including applying a priming of red oxide zinc chromate primer. | 100.00 | kg |
| 10 | Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm ..IS : 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. | 58.48 | sqm |
| 11 | Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. Size upto 200x300mm | 15.20 | sqm |
| 12 | Chequered precast cement concrete tiles 22mm thick in footpath & courtyard jointed with neat cement slurry mixed with pigment to match the shade of tile including cleaning of joint etc complete on 20 mm thick bed of cement mortar 1:4 (1 cement :4 coarse sand) : Light shade using white cement | 13.00 | sqm |
|  ASST. ENGINEER Nagar Palik Nigam, Bhilai | |  SUB ENGINEER Nagar Palik Nigam, Bhilai | |

कार्यपालन अभियंता
नगर पालिक निगम
भिलाई