

NAGAR PALIK NIGAM BHILAI

NIT

विधायक निधि अंतर्गत वार्ड क्र.—25 लाल पानी टंकी परिसर हाउसिंग बोर्ड भिलाई के पास सामुदायिक भवन निर्माण कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015

SN	PARTICULAR	QTY	UNIT
oraningou		VII	UNII
1	Excavation for all types and sizes of foundations, trenches and drains or forupto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.In all types of soil	,	
LAMP SERVICES		24.78	cum
2	Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete	Contraction of the Contraction o	
-	mixer in foundation, plinth and at ground level excluding cost of form work.		
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).		
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	0.00	
-		8.80	cum
3	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.1:11/2:3 (1 cement : 11/2 coarse sand : 3 graded stone aggregate 20mm nominal size).		
Alle Section Co.		21.13	cum
4	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete: Cold twisted bar / Hot rolled deformed steel		
-		1901.30	kg
5	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:		
5.a	Foundations, footings, base of columns and plinth beam in any shape and size.		
		30.80	sqm
5.b	Columns, Pillars, Piers and likes- rectangular or square in shape		
		71.00	sqm
5.c	Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)		
		130.58	sqm
5.d	Beams, lintels, cantilevers & walls		
		39.00	sqm
6	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 Cement : 6 Coarse Sand)		1
	The state of the s	4.92	cum
7	super structure Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 Cement : 6 Coarse Sand)		
		16.22	cum
	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.		
		31.80	cum
9	Providing and laying damp proof course (upto 50mm thick) with plain cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded crushed stone aggregate 20mm nominal size) including formwork		
		0.32	
0	Providing and fixing steel door with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of all necessary fittings complete including applying a priming coat of red oxide zinc chromate	127.20	kg
	primer		



		٠.
/	>	/
10	9	
1)
VA.		· r
		- 1

	(27)		
11	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frame of windows etc. including applying a priming coat of red oxide zinc chromate		A
	primer	43.20	kg
12			
12	6 mm thick cement plaster of mix:		
	In Cement Mortar 1:4 (1 cement : 4 fine sand)	81.08	sqm
13	12mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)	85.20	sqm
	·		
14	15mm thick cement plaster of mix:		
-	In Cement Mortar 1:6 (1 cement : 6 fine sand)	114.00	sqm
15	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and onforming to IS: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.		
-	matering pignetits etc. complete.	60.40	sqm
17	Distempering with acrylic washable distemper to give an even shade: on new work.(two or more coats)		
		166.28	sqm
18	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats)		
		114.00	sqm
19	Painting on new work (two or more coats) to give an even shade with.Premium synthetic enamel paint (2nd top most approved branded quality) to give an even shade.		
		21.36	sqm
	v.		
ASSTT.ENGINEER SUB ENGINEER			
	Nagar Palik Nigam, Bhilai Nagar Palik Nigam, Bhilai		1 12

कार्यपालन अभियंता कार पालक निगम भिलाई