


MUNICIPAL CORPORATION BHILAI (C.G.)


NIT


कार्य का नाम— वार्ड क्रं. 70 हुडको स्थित गुरुद्वारा के समीप शौचालय निर्माण कार्य।

As per Building sor 01-01-2015			
S.No.	Description and details of work	Qty.	unit
	Premium synthetic enamel paint		
1	Wall painting with acrylic luxury emulsion (plastic) paint of required shade to give an even shade. On old work (one or more coats)	110	sqm
2	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 12.3.1 40 mm thick	21	
		21	sqm
3	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	0.36	cum
4	Premium synthetic enamel paint	50	sqm
5	Removing following vitreous china sanitarywares carefully for re-use including stacking within 50 metres lead.		
a	Wash basin of all sizes and shapes each 30.50	1	each
b	16.53.2 Urinals of all sizes and shapes each 38.00	1	each
6	Providing and replacing broken vitreous china water closet (European type W.C. pan) including removing the broken water closet (European type W.C. pan) cutting and making good the walls and floors wherever required : 17.8.1 White pedestal type	1	each
7	Providing and fixing vitreous china wash basin with C.I. brackets, 32 mm C.P. brass waste of standard pattern, including painting of brackets, cutting and making good the walls wherever required : 18.17.1 White Size 550x450 mm	1	each
8	Providing and replacing broken vitreous china water closet squatting pan (Indian type) including removing the broken squatting pan and mortar, cutting and making good the walls and floors wherever required: 17.7.1 White Long pattern W.C. pan of size 580 mm	1	each
9	Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. 12.7.1 Size upto 200x300mm	84	sqm



10	Repairs to plaster in patches of area 2.5 sq. metres and under including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls with cement mortar 1:4 (1 cement : 4 fine sand) complete including disposal of rubbish to the dumping ground within 50metres lead : 17.1.1 Thickness upto 15mm	20	sqm
11	Applying cement slurry on R.C.C. slab or cement concrete work using 2.75 kg/ sqm for receiving cement concrete floor including roughening cleaning etc complete.	15	sqm
12	Providing and replacing broken floor tile with ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including removing the broken tile and mortar, pointing the joints with white cement mixed with matching pigment etc., complete. 17.2.1 Size 300x300mm	63	sqm


Asstt. Engineer
Municipal Corporation
Bhilai(C.G.)


Sub Engineer
Municipal Corporation
Bhilai (C.G.)