

11

NAGAR PALIK NIGAM BHILAI



NIT

वार्ड क्र.-14 रामनगर (नया वार्ड-26) शासकीय माध्यमिक शाला (22100715003) का संधारण कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015 & NON SOR ITEM

N.A. S.M. 2020

S.NO	PARTICULAR	QTY	UNIT
1	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to IS : 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.		
		511.31	sqm
2	Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.		
	Size upto 200x300mm	49.20	sqm
3	Providing and laying rectified ceramic glazed floor tiles of size 300x300mm and above conforming to IS : 15622 of approved make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.		
	Size 300x300mm	48.84	sqm
4	Wall painting with acrylic premium emulsion (plastic) manufactured with the cow dung processing emulsion paint of required shade to given an even shade. On old work (one or more coats)		
		679.20	sqm
5	Painting exterior surface with SMOOTH exterior emulsion paint of manufacturerd with cow dung processing to give protective and decorative finish including cleaning washing of surface etc. complete with: On old work (One or more coats applied @ 0.83 ltr/ 10 sqm)		
		737.64	sqm
6	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
		0.65	sqm
7	25mm thick cement concrete flooring with 1:2:4 cement concrete (1 cement : 2 coarse sand : 4 graded stone aggregate 12.5 mm nominal size) finished with floating cost of neat cement.		
		276.01	sqm
8	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)		
		107.85	sqm
9	Providing and making 12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand) sqm		
		50.85	sqm
10	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete includi g applying a priming coat of red oxide zinc chromate primer		
		799.20	kg
11	Painting on old work (one or more coats) to give an even shade with: Premium synthetic enamel paint		
		276.00	sqm

12	Providing and fixing water closet squatting pan (Indian type W.C. pan), 100mm sand cast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) conforming to IS : 7231, with flush bend and other fittings and fixtures complete including cutting and making good the walls and floors wherever required.		
	White Orissa pattern W.C. pan of size 580x440 mm each	5.00	sqm
13	Providing and fixing white vitreous china urinal basin with waste fitting as per IS : 2556, and other couplings in C.P. brass complete.		
	Flat back type urinal of size 460x380x250mm	5.00	each
14	Providing and fixing one piece construction white vitreous china squatting plate urinal with an integral rim longitudinal flushing pipe. each		
		5.00	each
15	Providing and fixing vitreous china wash basin with C.I. brackets, 32 mm C.P. brass waste of standard pattern, including painting of brackets, cutting and making good the walls wherever required		
	White Size 550x450 mm each	5.00	each
16	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, tamping and sweeping etc. complete of minimum compressive strength of 250 kg/sq.cm Plain normal coloured precast interlock concrete block		
		129.60	sqm
17	NON SOR ITEM Educational Wall Writing Work.	500.00	sqft
 ASST. ENGINEER Nagar Palik Nigam, Bhilai		 SUB ENGINEER Nagar Palik Nigam, Bhilai	