(8)

(3)

NAGAR NIGAM BHILAI

NIT

पार्षद निधि अंतर्गत वार्ड क्र.–24 हाउसिंग बोर्ड सांस्कृतिक भवन का संधारण एवं नयी सुविधाओं की व्यवस्था कार्य।

(AS PER BUILDING SOR 01.01.2015 & ELECTRICAL S.O.R. 01.06.2020)

S.NO	PARTICULAR	QTY	UNIT
1	Dismantling flag stone flooring laid in cement/lime mortar including stacking of serviceable material and disposal of nserviceable material within 50 metre lead.	80.00	Sqm.
2	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to IS : 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.	102.00	Sqm.
3	Providing and fixing aluminium composite panels in approved panel sizes, thickness and shape on aluminium frame work on face of building. (Frame to be paid separately)	40.50	Sqm.
4	Providing and fixing aluminium work for doors, windows, ventilators and partitions made out of extruded aluminium standard sections (main section with minimum 1.5mm thickness) conforming to IS: 733, IS: 1285 mitred and jointed mechanically including aluminium cleats, neoprene weather stripping gasket beveled edge beading, screws duly fixed in wall/ floor with fixing clips or hold fasteners or bolts and nuts as required aluminium sections shall be anodized transparent or dyed to approved shade according to IS: 1868, minimum anodic coating shall be of grade AC-15. (Glazing to be paid for separately:		
	For shutter of doors, windows & ventilators including providing and making provision for fixing of fitting wherever required including the cost of PVC/ neoprene gasket required (Fittings shall be paid for separately).	147.00	Kg.
5	Extra for providing and fixing tinted glass panes in aluminium door,window, ventilator shutters and partitions instead of float glass.	4.20	Sqm.
6	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with flat iron diagonals 20x5mm size with top and bottom rails of T-iron 40x40x6mm with 38mm steel pulleys complete with bolts, nuts, locking arrangement stoppers, handles including applying a priming coat of red oxide zinc chromate primer	10.85	Sqm.
7	Painting exterior surface with ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with:	74.40	Sqm.
8	Painting on new work (two or more coats) to give an even shade with:	74.40	Sqm.

ASSTT.ENGINEER
Nagar Palik Nigam, Bhilai

SUB ENGINEER
Nagar Palik Nigam, Bhilai