MUNICIPAL CORPORATION OF BHILAI NIT

विषय — जोन 05 के मार्केट एरिया में सी.सी. टी.वी की स्थापना कार्य में टयुबलर पोल स्थापित करने का कार्य।

S.N.	PARTICULERS OF ITEMS	Quantity	UOM	Rate	Amount
1	Supply of hot dip galvanized CONICAL POLEas per BSEN ISO 1461 standard with minimum coating thickness of 75 micron. The galvanizing shall be done in single dipping. The pole shaft shall be made from 3 mm sheet steel confirming to BSEN10025 having yield strength of 355N/ Sq mm and silicon content less than 0.04%. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. All Conical pole shafts shall be provided with the rigid flange plate manufacture from MSFE410 confirming to IS: 2062 of suitable thickness with provision for fixing 4 Nos 'J' type foundation bolts. The welding shall be done as per qualified MMAW process approved by Third Party Inspectionagency. The Conical Poles shall be designed to with stand the maximum wind speed as per IS875 part III. The top loading i.e. area and the weight of fixtures are to be considered to calculate maximum deflection of the pole and the same shall meet the requirement of BSEN 40-2- 1 &3. The Conical Poles shall have door of approximate 500 mm length 1000 1000 1000 1000 1000 1000 1000 10	19.00	each		
	Supply of 7 M Height Conical Pole diameter 75 mm at top 151 a bottom. Baseplate Size 250 x 250 x 16 mm foundation bolt 750 mm long Mx20 EN 8 grade	t	=		

नगर पालिक निगम, भिलाई