MUNICIPAL CORPORATION OF BHILAI

वार्ड क्र. 44 लक्ष्मीनारायण नगर में शाहनी बस्ती के समीप सौंदर्यीकरण कार्य।

As Per PWD Building SOR 01.01.2015, Electrical SOR 01.06.2020 & NON SOR ITEM

N	PARTICULERS OF ITEMS	QTY.	UNIT
	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose	22.66	C
1	including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the	29.66	Cum
	excavated area), including dressing and leveling of pits. In all types of soil		
	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete	2.06	Cum
2	mixer in all works upto plinth level excluding cost of form work.	3.06	Cuiti
	1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size).		
	Providing and placing in position angle iron post and strut of required size including bottom to be split		Kg
3	and bent at right angle in opposite direction for required length and drilling holes upto 10 mm dia as	201.55	
,	per requirement including priming coat with red oxide zinc chromate primer and placing the post/ strut		
	in cement concrete block.		
	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete	4.80	Cum
4	mixer in all works upto plinth level excluding cost of form work.	4.00	00
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).		
	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete	16.76	Cum
5	mixer in all works upto plinth level excluding cost of form work.	10.70	
	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting,	838.40	Kg
6	bending, binding etc. complete as per drawings including cost of binding wire all complete:Thermo-	0.500	
	Mechanically treated bars Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and		
	Steel work welded in built up sections/ framed work including cutting, holsting, holst	242.12	
7	applying a priming coat of red oxide zinc	349.12	Kg
	chromate primer. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works.		
	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing		
	etc. complete and including its removal at all levels, for: (A) Foundations, footings, base of columns	167.68	sqm
8	and plinth beam in any shape and size.		,
	Providing and fixing in position chain linked steel wire fabric made of 4 mm dia G.I. wire of required		
	width in mesh to concrete/ wooden/ angle iron posts including securing and screwing with 2mm dia	60.00	1
9	G.I. wire, G.I. staples, G.I.U-nails or steel pins etc., complete.	60.00	sqm
	Aperture 50x50mm		
	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not		
10		43.20	Cum
10	dressing etc. complete.		
	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305		
	sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick		sqm
11		96.00	
	minimum compressive strength of 250 kg/sq.cm	70.00	
	Pigment Coloured (rubber mould) precast interlock concrete blocks		
	Supplying and stacking of good earth at site including royalty, loading, unloading and carriage upto 5		
12		30.00	Cum
	reduced by 20% for payment).		
	Supplying and stacking at site well decayed cow dung manure from approved source, including		
13	Symmetry are a rain (marate measured in stacks will be reduced by 8% lor	5.00	Cum
	payment).	_ ,	
14	Spreading of sludge, dump manure or/and good earth in required thickness (Cost of sludge, dump	40.00	
	manure or/ and good earth to be paid separately).	40.00	Cum
1 4	Providing and planting following herbs in garden including preparation of soil, base plantation,		
15	providing and spreading different fertilizers, soil and sand:	560	Each
	Hedges like Alife, Dorenta, Tikoma etc	- 50	Lacii
10	, see (e jeta ola)	25	Each
	Hibiscus (Flower)/ Rose		Lacii
11		80	Each

SN	PARTICULERS OF ITEMS	QTY.	UNIT
Grassi the grand fir separa	rass forms a thick lawn free from weeds it for mowing including supplying good earth if needed (the good earth shall be paid for ately).	150.00	sqm
Carryi prope interp	ws 5 cm apart in either direction. Ving out the resistivity survey by VES method using Schlumberger configuration for locating the cr spot for drilling of tube well within the selected habitation, including photography, pretation of resistivity data and submission of report in the desired format along with resistivity ngs, necessary graph and photographs. (only successful point is payable)	1	Point
casing prescr 21 submi machi depth	ng/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for g/ strainer pipe, by suitable method ribed in IS: 2800 (part I), including collecting samples from different strata, preparing and itting strata chart/bore log, including hire & running charges of all equipments, tools, plants & ineries required for the job, all complete as per direction of Engineer—in-charge upto 90 metre below ground level.	45.00	Mtr.
	y strata including Boulders. 150 mm nominal dia	1.50	Mtr.
Suppl pipe (23 1&Par fitting	lying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Partart-2) 1992 with IVth of reputed & approved make, including required hire & labour charges, gs & accessories, all complete, for all depths, as per direction of Engineer- in-charge. 150 mm nal dia	47.00	Mtr.
casing prescr charge of Eng	ng/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for g/ strainer pipe, by suitable method ribed in IS: 2800 (part I), including collecting samples from different strata, preparing and ges of all equipments, tools, plants & machineries required for the job, all complete as per direction agineer-in-charge beyond 90 metre & upto 150 metre depth below ground level. y strata including Boulders. 150 mm nominal dia	44.00	Mtr.
25 housii	ding and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well ing/ casing pipe, removable as per requirement, all complete for bore well of: nm nominal dia	1	Each
Provid 26 excav	ding and laying in trenches G.I. pipes medium class complete with G.I. fittings including vation of trenches, refilling the same and testing of joints complete: m dia. nominal bore	88.00	Mtr.
Provid IS:893 requir	iding and fixing 15 mm nominal bore C.P. brass fittings of approved make and conforming to 31 including C.P. brass extension if	4	Each
25 mi	iding and fixing brass/ gun metal gate valve with C.I. wheel of approved quality (screwed end): m nominal bore	4	Each
29 at bot Desig	oly Of Swaged steel tubular Pole as per IS 2713 with base plate of size 300 x 3000 x 6 mm welded attom specified height including painting with one coat of red oxide zinc chromate primer. gnation 410 SP-26 height 9.00 metre	20	Each
30 Stone	tion of steel tubular pole or rail pole in cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded e aggregate 40mm nominal size) foundation including excavation & refilling etc as required of 7 e to 10 metre	20	Each
31 2 No	oly & fixing water tight terminal box made of 1.6 mm thick M S Sheet with detachable gland plate of the connection of th	20	Each
	ply & Making end termination with brass compression gland & aluminum lugs for following size ored aluminum conductor power cable of 1.1 KV grade as required 3 x 25 sq.mm	40	Each
33 grad	ply & fixing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV de power cable core/lead pressed with high pressure cramping tool including connection to switch to switch switch described by the switch switch as required 25 sq.mm.	80	Each

1	PARTICULERS OF ITEMS	QTY.	UNIT	Rate
34	Supply & Fixing GI Pipe Along With wall or pole/support with 2 nos. MS clamp for protection of underground cable in approved manner including bolts & nuts or metal dash fasteners complete as required 40 mm dia	200.00	Meter	
35	Painting new steel & other metallic surface with red oxide zinc chromate primer paint complete with supply of material labour etc including preparation of surface	126.00	Sqm	
36	Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as required. Double Over Hang 1.50 metre Long	20	Each	
37	Painting wood steel & other metallic surface with aluminum paint complete with material & labour including preparation of surface	126.00	Sqm	
38	Providing & Laying Cast In situ Cement Concrete 1:3:6 graded stone aggregate 40 mm nominal size foundation including mixing with mechanical mixer compacting with vibrator finishing & currying etc complete but excluding formwork	5.09	Cum	
39	Providing timber steel formwork for cement concrete work at all levels including removing of the same	16.96	Cum	
40	Earthing with G.1. earth pipe 4.5 m long 40 mm dia including accessories & providing masonary enclosure with cover plate having locking arrangement watering pipe etc (But without charcoal & salt) as required	20	Set	
41	Supplying and drawing following sizes of FR PVC insulated copper conductor, single core cable in the existing surface/ concealed, steel/ PVC conduit/ PVC casing caping as required. 3×2.50 sq.mm	900.00	Sqm	
42	Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately). 32 amps	60	Each	
43	Supplying, installation, testing and commissioning of following 230/250 volts LED street light fitting with all accessories like driver, heat sink made of die cast aluminium with IP 66 protection and 5 KV surge protection on pole bracket complete as required and furnishing 2 Yrs Guarantee certificate from manufacturer. 90 watt	40	Each	
44	Supplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc as required. 2 x 16 sq. mm	1000.00	Meter	
45	NON SOR ITEM Providing & Planting well developed & healthy (5' and above) orna mental plants with digging holes soil filling & chemical & biological treatment like ficus cycas chhatim, bottle palm, supari palm, musanda & avenue palm, tree including 6th month maintenance till well established as directed Engineer In charge	50	Each	
46	NON SOR ITEM Providing & Planting well established flowering & orna mental plants or shrubs like nerium, bougainvillia, crotons, vidhya etc. with digging holes & chemical treatment including 6th month maintenance till well established as directed Engineer In charge	25	Each	
47	NON SOR ITEM Providing & Planting well developed succulent healthy orna mental plants with digging chemical treatment like thuja, cycas, lolina etc, including 6th month maintenance till well established as directed Engineer In charge	15	Each	

Executive Engineer Municiapal Corporation Bhilai

Assistant Engineer **Municipal Corporation** Bhilai

Sub Engineer Municipal Corporation Bhilai