## MUNICIPAL CORPORATION OF BHILAI

<u>NIT</u>

कार्य का नाम— वार्ड सेक्टर 10 जोनल मार्केट के समीप बोर खनन सह पाईप लाइन विस्तारीकरण कार्य

- 19	Carrying out the resistivity survey by VES method wing G. H.	Quantity	UOM
	Carrying out the resistivity survey by VES method using Schlumberger configuration for ocating the proper spot for drilling of tube well within the selected habitation, including shotography, interpretation of resistivity data and submission of report in the desired format along with resistivity readings, necessary graph and photographs. (only successful point is Boring/drilling bore well posterior to the desired format payable)	1	Point
٠,	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by suitable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer-incharge upto 90 metre depth below ground level.		197
	All types of soil 150 mm nominal dia	30	Metre
	Rocky strata including Boulders 150 mm nominal dia	80.00	Metre
3	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by suitable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge beyond 90 metre & upto 150 metre depth below ground level. Rocky strata including Boulders 150 mm nominal dia	37	Metre
4	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all depths, as per direction of Engineer- in-charge. 150 mm nominal dia	26	Metre
4	Development of tube well in accordance with IS: 2800 (part I) and IS: 11189, to establish maximum rate of usable water yield without sand content (beyond permissible limit), with required capacity air compressor, running the compressor for hire & labour charges of air required capacity air compressor, running the compressor for hire & labour charges.	4	Hrs
	Providing and fixing suitable size threaded mild steel cap of spot wester providing and fixing suitable size threaded mild steel cap of spot wester providing providin	1	Each
100000000000000000000000000000000000000	Electrical SOR 01.06.2020  Supplying, installation, testing and commissioning of submersible pump set for water supply system with submersible motor directly coupled to multi-stage submersible pump of specified system with submersible motor directly coupled to multi-stage submersible pump of specified system with submersible motor directly coupled to multi-stage submersible pump of specified system with submersible discharge capacity, head, delivery size in existing bore well including 2 sets of suitable size discharge capacity, head, delivery size in existing bore well including 2 sets of suitable size holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible holding clamps made out of 50 mm MS flat, connection with s	1	Each
7	Supply, installation, testing and commissioning of 5-7.5 HP 3 phase submersible motor starter  Supply, installation, testing and commissioning of 5-7.5 HP 3 phase submersible motor starter  cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and compression floor floor mounted type made out of not less than 1.6 mm thick MS sheet and compression floor	1	Each

	Providing following size ISI marked FR PVC insulated, PVC sheathed, 3 core submersible copper conductor wire and IS: 694 (2010) 2.5 sq. mm	50	detre
10	sockets in the suction/ delivery line including cutting and threading etc. as per specification. 25 mm dia.	25	letre
	Providing and laying in trenches G.I. pipes medium class complete with G.I. fittings including excavation of trenches, refilling the same and testing of joints complete:	inger i waa am an	
12	50 mm dia. nominal bore	50	Metre
13	40 mm dia. nominal bore	50	Metre
14	25 mm dia. nominal bore	70	Metre
15	15 mm dia. nominal bore	20	Metre
	Providing and fixing brass/ gun metal gate valve with C.I. wheel of approved quality (screwed end):50 mm nominal bore	2	Each
16	Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved quality: Bib cock (250 grams)	15	each
17	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	1000	litre

Asstt. Engineer
Municipal Corporation
Bhilai(C.G.)

Sub Engineer

Municipal Corporation

Bhilai(C.G.)