NAGAR NIGAM BHILAI

NIT

जोन क्र.-02 वैशालीनगर क्षेत्रांतर्गत स्थित पंप हाउस का संघारण कार्य। NG SOR 01.01.2015 & ELECTRICAL SOR 01.06.2020)

N. Carlotte	(AS PER BUILDING SOR 01.01.2015 & ELECTRICAL SOR 01.00.2020)	QTY	UNIT
0	DESCRIPTION OF THE PROPERTY OF	-	
1	Demolishing R.C.C. work including stacking of steel bars and disposal of		
•	unserviceable material within 50 metre lead.	5.12	cum
-,	Dismantling lime/ cement plaster or skirting at any height raking out joints and cleaning the surface for	1	
2	plaster including disposal of rubbish within 50 metres lead.	170.70	sqm
_		170.70	sqiii
3	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area),		
	including dressing and leveling of pits. In all types of soils.	17.28	cum
	La La consegue que no consegue		
4	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using		
	to all works upto plinth level excluding COSL 01 101111 WOLK.	7.75	cum
	1. 11/ 2 (1 sement 11/ coarse cand : 3 graded stone apprepaie 20iiiii iioniiiai 522).		
5	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, oinding etc. complete as per drawings including cost of binding wire in foundation and plinth		
	all complete:	620.30	kg
	Thermo-Mechanically treated bars FE 415 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc.		
	learn late and including its removal at all levels, 10r; Foundations, toolings, bases of column party and including its removal at all levels, 10r; Foundations, toolings, bases of column party and including its removal at all levels.		
	beam, curtain wall in any shape and size and all type of wall below plinth level.	22.48	sqm
	a L. A graded stone		
	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone		
	aggregate 20mm) finished with a floating coat of neat cement.	64.60	sqm
	11.1	04.00	3411
	50 mm thick Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix:		
	In Cement Mortar 1:5 (1 cement : 5 fine sand)	200.00	sqm
	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of		
	surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and	200.00	sqn
:	a On new work (1 wo or more coats appried @ 1.45 km 10 squite views		
	including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	100.00	sqn
	b On old work (One or more coats applied @ 0.83 ltr/ 10 sqm) O Providing and laying nominal mix plair, coment concrete with crushed stone aggregate using concrete		
1	Ol Providing and laying nominal mix plain content concrete with crushed stone aggregate asing contents		
	inixer in all works upto plinth level excluding cost of form work.	2.66	cun
	1:4:8 (1 cement : 4 coatse sand : 8 graded stone aggregate 40mm		
	nominal size). 1 Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to	100.00	kg
	1 Providing and fixing M.S. griff of approved pattern made of this that of square steel frame of windows etc.C34including applying a priming coat welded to frame with all necessary		
	steel frame of windows etc. C34including applying a printing coat werded to make the state of th		
	fitting complete including applying a priming of red oxide zinc chromate primer.		
	2 Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces		
1	2 Providing and fixing steel door/ window with ivi.s. sheet filling these, frame of angle from diagonal orders		
	of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary		
	fittings complete including applying a priming coat of red oxide zinc chromate primer.	450.00	kg
		-	_
	3 Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	37.20	sqn
1	4 Providing & fixing wooden electrice pannel board/Cutout etc. as per Electrical S.O.R. 01.06.2020		LS

ASSTT.ENGINEER

Nagar Palik Nigam, Bhilai

SUB ENGINEER

Nagar Palik Nigam, Bhilai