MUNICIPAL CORPORATION BHILAI (C.G.)

NIT

का नाम— वार्ड 69 सेक्टर 09 सड़क 28 काली मंदिर के समीप पेवर ब्लाक लगाने एवं एक नग बोर खनन कार्य।

—— <u>T</u>	Description and details of work ELEC SOF	2020 & Buildir	Unit
		Qty.	Unit
l I	Boring/drilling bore well perfectly vertical for the specified depth suitable to	-	
1 S	eceive required dia for casing/ strainer pipe, by itable method prescribed in IS:		
	boo (part 1), including collecting samples from different strate propaging and	20.00	Rmt
	domitting strate chargoole log, including hire & running charges of all		
	equipments, tools, plants & machineries required for the job, all complete as per		
C	irection of Engineer—in-charge upto 90 metre		
	lenth below ground level. All types of soil 150MM DIA	22.00	Rmt
21	Rocky strata including Boulder 150MM DIA	22.00	
	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI		
1	marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted		Rmt
3	with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date	20.00	Kilit
1	amendments), of reputed & approved make, including required hire & labour	1	
1	charges, fittings & accessories, all complete, for all depths, as per direction of		
	Engineer in charge 150mm nominal size dia		
	Providing and fixing suitable size threaded mild steel cap or spot welded plate to	1.00	each
4	the top of bore well housing/ casing pipe, removable as per requirement, and	1.00	
.1	late for hore well of: 150mm nominal size dia		
	Providing and fixing on wall surface G.I. pipes medium class complete with G.I.		
5	fittings and clamps, including cutting, making good the walls etc. and testing of		
	ioints complete:	55.00	Rmt
a	25 mm dia. nominal bore	51.00	Rmt
b	50 mm dia. nominal bore	31.00	
	Providing ISI Mark 32 mm dia G.I. (B class) riser pipe and M. plunger rod in 3	21.00	Rmt
6	1 to 1 and one and as ner IS 1739 (Part I) 1970 With up to date	21.00	
v	amendments and socket as per IS: 2062/1990 up to date amendment Excavation for all types and sizes of foundations, trenches and drains or for		
	Excavation for all types and sizes of foundations, trenches and drains of the Excavated stuff unto 1.5 m lift and		
_	any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing	99.8	
7	lead upto 50m (at least 5m away from the excavated area), merdanig at 550m		
	and leveling of pits.(In all types of soils.) Providing and laying nominal mix plain cement concrete with crushed stone		
	Providing and laying nominal mix plant center concrete with of about or aggregate using concrete mixer in all works upto plinth level excluding cost of	32.72	cum
8	aggregate using concrete mixer in an works upto pinter rever streaming over a	32.72	00
	form work. Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS		
	12894-2002 of class designation 4.0 in foundation and plinth in 7.5.4 Cement	2.24	Cum
9	Mortar 1:6 (1 cement: 6 coarse sand)	2.24	Cum
	Providing and placing on terrace (at all floor levels) polyethylene water		
	storage tank ISI: 12701 marked with cover and suitable locking arrangement		
10	and making necessary holes for inlet, outlet and overflow pipes but without	1000.00	ltr
	fittings and the base support for tank		
	Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved		
11	quality: 19.13.1 Bib cock (250 grams)	15.00	each
	19.12 Providing and fixing G.I. Union in existing G.I. pipe line, cutting and		
12	threading the pipe and making long screws including excavation, refilling the		
	earth or cutting of wall and making good the same complete wherever		
	required:		-
a	19.12.2 20 mm nominal bore.	2.00	each
	19.12.3 25 mm nominal bore.		
b		2.00	each
13	19.14 Providing and fixing 15 mm nominal bore C.P. brass fittings of approved		
	make and comorning to 10.0001 including C.P. brass extension if required.		
	19.14.6 Stop cock (concealed) (600 grams)		-
a		2.00	each
b	19.15 Providing and fixing stainless steel drain jali of approved make/quality.	3.00	each

14	3.1 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 3.1.5 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	6.97	Cli m
15	12.3 Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 12.3.1 40 mm thick	6.00	sqm
16	Supplying, installation, testing and commissioning of submersible pump set for water supply system with submersible motor directly coupled to multistage submersible pump of specified discharge capacity, head, delivery size in existing bore well including 2 sets of suitable size holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible cable of standard length etc. as required.1.5.0 HP, single phase	1.00	Each
17	Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible motor starter cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following panel mounting switchgears there in including connection inter-connection etc. as required. a) Phase indicating lamps with fuses and toggle switches 1 set b) 1/2/3 HP 1 phase DOL starter with over load and no volt relay 1 No c) 25 A "C" curve DPMCB 1 No d) Voltmeter 0-250 V 1 set e) Ammeter 0-10 A 1 set	*	Each
18	Supplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc as required.		Metre
19	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.	32.40	cum
19	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping and sweeping etc. complete of minimum compressive strength of 250 kg/sq.cm Pigment Coloured (rubber mould) precast interlock concrete blocks	324.00	sqm
20	Carriage by mechanical transport upto 5 km lead: 1.26.1 Earth	58.32	cum

Asstt. Engineer Municipal Corporation Bhilai(C.G.)

Sub. Engineer Municipal Corporation Bhilai(C.G.)