

NAGAR NIGAM BHILAI

NIT

कार्य का नाम :— 02 नग बोर खनन निर्माण, वार्ड कमांक 32 विधानसभा वैशाली नगर

S.1	AS PER PWD BUILDING S.O.R 01.01.2015 and Electrical SOR 2016 & No				
	FARIUILAR		TY U		
1	Carrying out the resistivity survey by VES method using Schlumberger configuration for locating the prop spot for drilling of tube well within the selected habitation, including photography, interpretation of resistivity data and submission of report in the desired format along with resistivity readings, necessary graph and photographs. (only successful point is payable)	er 2.0	00 p		
2	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing strainer pipe, by suitable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge upto 90 metre depth below ground level. All types of soil 150 mm dia.	:	00 me		
3	Rocky strata including Boulders. 150 mm dia.	150.0	00 me		
4	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/strainer pipe, by suitable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge beyond metre & upto 150 metre depth below ground level. Rocky strata including Boulders. 150 mm dia.				
5	housing/ casing pipe, removable as per requirement, all complete for the top of bore well	2.00	eac		
5	(Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all depths, as per direction of Engineer- in-charge. 150 mm	60.00			
	Supplying, installation, testing and commissioning of submersible pump set for water supply system with submersible motor directly coupled to multi-stage submersible pump of specified discharge capacity, head, delivery size in existing bore well including 2 sets of suitable size holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible cable of standard length etc. as per specification and IS: 694 (2010). Note: submersible Cable should be rust proof, safe from oil / Grease and under water Chemical / abrasion Resistant. 1.5 HP, single phase	2.00	each		
i V	Supply, installation, testing and commissioning of 1-3 HP I phase submersible motor starter cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following panel mounting switchgears there in including connection interconnection etc. as required. a) Phase indicating lamps with fuses and toggle switches 1 set b) 1/2/3 HP I phase DOL starter with over load and no solve the control of the con	2.00	Each		
a N	ION SOR ITEM	200.00	MT		
P C	roviding ISI Mark 32 mm dia Black H.D.P.E Roll Pipe with Bottom and Top Socket Assembly Fiting all	00.00	meter		
R	2 phase energy meter connection with 3x10 sqmm Service Cable Inculding all installation Charge	2.00	No		
Ex dis	scavation for all types and sizes of foundations, trenches and drains or for any other purpose including sposal of excavated stuff upto 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and lead upto 50m (at least 5m away from the except to 1.2 m lift and	3.68	Cum		



S.N.	PARTICULAR	QTY	UNIT
2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	0.26	Cum
3	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	2.12	Cum
4	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.	0.30	Cum
5	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete: Thermo-Mechanically treated bars FE 415	24.00	Kg
6	Supplying, filling, spreading & leveling stone boulders/ Gravels/ Coarse sand, in recharge pit, in the required layers and thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge. (excavation of pit will be paid separately). Stone boulders of size range 5 cm to 20 cm, in recharge pit	1.20	Cum
7	Gravels of size range 5 mm to 10 mm, over the existing layer of boulders	0.96	Cum
8	Coarse sand of size range 1.2 mm to 2 mm over existing layer of gravel	0.72	Cum
9	Providing and fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS: 13592 (4kg/sqcm) including required couplers, jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion etc complete. 110 mm dia pipe.	11.00	mtr

कार्यपालन अभियन्ता नगर पालिक निगम, मिलाई सहायक अभियन्ता नगर पालिक निगम, मिलाई

जप अभियन्ता नगर पालिक निगम, भिलाई