UNICIPAL CORPORATION OF BHILAI

65, सेक्टर-10, सडक-35, सेंट्रल एवंन्यु रोड के सामने स्थित पंतर ब्लाक लगाने का कार्य।

100000000000000000000000000000000000000			
RTI	CULERS OF ITEMS	Quantity	UOM
	CULERS OF ITEMS ing and making 6mm thick cement plaster of mix:In Cement mortar 1:3 (1 cement : 3 fine	100	SQM
- (cand)	ing and making 6mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine	100	SQM
3 Provid	ing and making 6mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine	100	SQM
	spering with acrylic washable distemper to give an even shade. On new work (Two or more	200	SQM
5 shade a	ng new exterior surface (Two or more coats) with PREMIUM TEXTURED paint of required as per manufacturer's specifications to give tive and decorative finish including cleaning washing of surface etc.	100	SQM
6 Paintin	ete with: ng on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	52.02	SQM
7 proces	ng exterior surface with SMOOTH exterior emulsion paint manufactured with cow dung ssing to give protective and decorative finish including plete with:		
	www. (Two or more coats applied @ 1.43 ltr/10 sqm over)	580	SQM
9 On ol	d work (one or more coats applied @ 0.83 ltr/10 sqm over)	580	SQM
Provide of app	lising and fixing ceramic glazed wall tiles conforming to IS: 15622 broved make, colours, shades and size on wall and dados over 12 blick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and ng with grey cement slurry @ 3.3kg per sqm including pointing in cement mixed with matching pigment complete. Size upto 200x300mm	80	SQM
Provide printi 1562 below coars	ding and laying vitrified floor tiles with double charge/ multi charge ng with water absorption less than 0.5% and conforming to IS: 2 of approved make in all colours and shades and size mentioned v (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 se sand) including grouting the joints with white cement and hing pigments etc. complete Size 600x600mm	90	SQM
Prov 12 inclu	iding and constructing soak pit 1.20x1.20x1.20m filled with brickbats iding S.W. drain pipe 100 mm diameter and 1.20 m long complete as standard design	1	SQM
13 Exc incl exc	avation for all types and sizes of foundations, trenches and drains or for any other purpose uding disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the avated area), including dressing and leveling of pits (In all types of soils.)	30.00	cum
14 exc dres	widing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not eeding 20cm in depth consolidating each deposited layer by ramming and watering, including ssing etc. complete.	15.00	Cum
15 con coa	viding and laying nominal mix plain cement concrete with crushed stone aggregate using crete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 1 rse sand : 4 graded stone aggregate nominal size).	15.00	Cum
16 thic com	viding & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 m) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm ik filled by fine sand including leveling with surface vibrator, temping and sweeping etc. aplete of minimum compressive strength of 250 kg/sq.cm Pigment Coloured (rubber mould) cast interlock concrete blocks	150.00	SQM
coar	viding and laying nominal mix plain cement concrete with crushed stone aggregate using crete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement : 1½ see sand : 3 graded stone aggregate 20mm nominal size).	3.00	Cum
18 Carr 1.26	riage by mechanical transport upto 5 km lead: 1 Earth	27.00	Cum
	4% for electric wor	k	
4% for sanitary work			
	4% for water supply work		

Asstt. Engineer **Municipal Corporation** Bhilai(C.G.)

Sub Engineer Municipal Corporation Bhilai(C.G.)