MUNICIPAL CORPORATION BHILAI (C.G.)

कार्य का नाम :- 02 नग बोर खनन निर्माण कार्य , इन्द्रजीत घर के पास एवं मुरूम खदान तालाब के पास वार्ड कमांक 11 विधानसभा वैशाली नगर

Pwd Building Sor 01.01.2015 & Electric Sor 01.06.2020 & Non Sor

S.No.	Pwd Building Sor 01.01.2015 & Electron and details of work	Qty.	Unit
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.2 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soil	1.84	Cum
2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement: 4 coarse sand: 8 graded stone aggregate 40mm nominal size).	0.13	Cum
3	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	1.06	Cum
4	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work	0.15	Cum
5	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.	12.00	Kg
6	Supplying, filling, spreading & leveling stone boulders/ Gravels/ Coarse sand, in recharge pit, in the required layers and thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge. (excavation of pit will be paid separately). Stone boulders of size range 5 cm to 20 cm, in recharge pit	0.60	Cum
	separately). Stolle country	0.48	Cum
7	Gravels of size range 5 mm to 10 mm, over the existing layer of boulders	0.36	Cum
8	Coarse sand of size range 1.2 mm to 2 mm to 3		
9	Providing and fixing on wall face of thirder from 6.7 states and fixing on wall face of thirder from 6.7 states and fixing on wall face of thirder from 7.8 states and 7.8 states are fixed provided and fixing and fixing and fixing on wall face of thirder from 8.1 states are fixed from 8.1 states and 8.1 states are fixed from 8.1	5.50	Mtr.
10	Carrying out the resistivity survey by VES method using Schlumberger configuration for locating the proper spot for drilling of tube well within the selected habitation, including photography, interpretation of resistivity data submission of report in the desired format along with resistivity readings, necessary graph and photographs. (only successful point is payable)	and 2.00	0 Point
11	Boring/drilling bore well perfectly vertical for the specified depth suitable receive required dia for casing/ strainer pipe, by suitable method prescribed IS: 2800 (part I), including collecting samples from different strata, preparant submitting strata chart/bore log, including hire & running charges of a and submitting strata chart/bore log, including hire & running charges of a plants & machineries required for the job, all complete	ing II 50 as	.00 Metre
	Rocky strata including Boulders.	15	0.00 Meta
	125 mm dia.		

S.No.	Description and details of work	Otv	Uit
12	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by suitable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge upto 90 metre depth below ground level.	80.00	Metre
13	Providing and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well housing/ casing pipe, removable as per requirement, all complete for bore well of: 150 mm dia	2	Each
14	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Upto-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all depths, as per direction of Engineer- in-charge.	60.00	Metre
15	Supplying, installation, testing and commissioning of submersible pump set for water supply system with submersible motor directly coupled to multi-stage submersible pump of specified discharge capacity, head, delivery size in existing bore well including 2 sets of suitable size holding clamps made out of 50 mm X 6 mm MS flat, connection with suitable submersible cable of standard length etc. as per specification and IS: 694 (2010). Note: submersible Cable should be rust proof, safe from oil / Grease and under water Chemical / abrasion Resistant.	2	Each
16 I St a) b) c)	Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible notor starter cum control wall/ floor mounted type made out of not less than a commission of following panel mounting witchgears there in including connection interconnection etc. as required. Phase indicating lamps with fuses and toggle switches 1 set 1/2/3 HP 1 phase DOL starter with over load and no volt relay 1 No 25 A "C" curve DPMCB 1 No Voltmeter 0-250 V 1 set	2.00	Each
7 (20	pplying, laying and fixing following size submersible cable along with /PVC/HDFC pipe line or laid in ground etc as per specification and IS: 694 lol). Note: Cable should be rust proof, safe from oil / Grease and under ter Chemical / abrasion Resistant.	200.00	Metre
	N SOR ITEM		
1.500	viding ISI Mark 32 mm dia Black H.D.P.E Roll Pipe with Bottom and Top ket Assembly Fiting all Complete	200.00	M
10 1	ase energy meter connection with 4 Core 16mm Service Cable Inculding		Metre

Executive Engineer **Municipal Corporation** Bhilai (C.G)

Asstt. Engineer **Municipal Corporation** Bhilai (C.G)

M

Sub. Engineer **Municipal Corporatio** Bhilai (C.C.)

का

हुआ

1.01

3.0 कृति

. Я