

NAGAR PALIK NIGAM BHILAI
NIT


पार्षद निधि अंतर्गत वार्ड क्र.-25 जवाहर नगर सार्वजनिक भवन का संधारण एवं नयी सुविधा उपलब्ध कराने का कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015 & ELECTRICAL SOR 01.06.2020

SN	PARTICULAR	QTY	UNIT
1	Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and even.	202.50	sqm
2	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	202.50	sqm
3	Distemping with acrylic washable distemper to give an even shade. On new work (Two or more coats)	90.00	sqm
4	Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	24.00	sqm
5	Providing and making 12mm thick cement plaster of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand)	40.00	sqm
6	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)	70.00	sqm
7	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to IS : 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.	17.00	sqm
8	Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. Size upto 200x300mm	18.75	sqm
9	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 40 mm thick	29.20	sqm


ASSTT.ENGINEER

Nagar Palik Nigam, Bhilai


SUB ENGINEER

Nagar Palik Nigam, Bhilai