MUNICIPAL CORPORATION BHILAI (C.G.) NIT

Name of work :- जोन क्र. 05 अंतर्गत वार्ड क्र. 66 सेक्टर 07 पूर्व भिलाई में पेयजल हेतु 01

.no.	Docari et ELEC SO	R 2020 & Building SOR 01.01.2015	
		Qty.	Unit
	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by itable method prescribed in IS: 2800 (part 1), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge upto 90 metre depth below ground level. All types of soil 150MM DIA	18.00	Rmt
2	Rocky strata including Boulder 150MM DIA	80.00	Rmt
3	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all depths, as per direction of Engineer-in-charge. 150mm nominal size dia	19.00	Rmt
4	Providing and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well housing/ casing pipe, removable as per requirement, all complete for bore well of: 150mm nominal size dia	1.00	each
5	Providing ISI Mark 32 mm dia G.I. (B class) riser pipe and M. plunger rod in 3 meter length socketed on one end as per IS: 1239 (Part I) 1990 with up to date amendments and socket as per IS: 2062/1990 up to date amendment	21.00	Rmt
6	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.(In all types of soils)	5.00	cum
7	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto	0.32	cum
8	12.3 Cement concrete flooring with cement concrete 1:2.4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 12.3.1 40 mm thick	4.00	sqm
9	Supplying, installation, testing and commissioning of submersible pump set for water supply system with submersible moto directly coupled to multi-stage submersible pump of specified discharge capacity, head, delivery size in existing bore we including 2 sets of suitable size holding clamps made out of 5 mm X 6 mm MS flat, connection with suitable submersible cable of standard length etc. as required.1.5.0 HP, single phase	1.00	Each

10	Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible motor starter cum control wall/floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following panel mounting switchgears there in including connection inter connection etc. as required a) Phase indicating lamps with hises and toggle switches 1 set b) 1/2/3 HP 1 phase DOL starter with over load and no volt relay 1 No c) 25 A "C" curve DPMCB 1 No d) Voltmeter 0-250 V 1 set e) Ammeter 0-10 A 1 set		Each
11	Supplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc as required.	30.00	Metre

Asst Engineer

Municipal Corporation

Bhilai(C.G.)

Supergineer
Municipal Corporation
Bhilai(C.G.)