


MUNICIPAL CORPORATION OF BHILAI

NIT

वार्ड क्र. 40 शहीद चुम्भन यादव वार्ड अंतर्गत लक्ष्मण नगर एवं शंकर नगर में सामुदायिक नलों का संधारण एवं अतिरिक्त सुविधा प्रदान करने का कार्य। (पार्षद निर्दिष्ट)

(As Per PWD Building Schedule)

S.N.	PARTICULARS OF ITEMS	Quantity	UOM
1	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size)	0.68	Cum
2	Dismantling terrazzo or mosaic or glazed vitreous or patent cement or tiled flooring or dado skirting of any thickness without sub base.	99.17	Sqm
3	Demolishing cement concrete including disposal of material within 50 metre lead. 1:3:6 or richer mix	2.43	Cum
4	Dismantling lime/ cement plaster or skirting at any height raking out joints and cleaning the surface for plaster including disposal of rubbish within 50 metres lead.	99.17	Sqm
5	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	2.14	Cum
6	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of 1:5 In Cement Mortar 1:5 (1 cement : 5 fine sand)	99.17	Sqm
7	Providing and laying vitrified floor tiles with double charge/ multi charge printing with water absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Size 600x600mm	30.47	Sqm
8	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 40 mm thick	35.65	Sqm
9	Applying one coat of cement primer on wall surface (applied @ 0.80 ltrs/10 sqm) complete.	99.17	Sqm
10	Providing and applying 2mm thick ready mix exterior grade putty (Manufactured with cow dung processing) on walls to make the surface smooth and even.	99.17	Sqm
11	Painting exterior surface with SMOOTH exterior emulsion paint manufactured with th cow dung processing to give protective and decorative finish including cleaning washing of surface etc. complete with : On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over)	99.17	Sqm
12	Providing stainless steel railing/ grilli made of S.S. flats, hollow S.S. pipe or square rectangular sections of approved design fixing in stair case, balcony or other places with metal fasteners and stainless steel bolts etc complete. SS Grade 304	216.12	Kg


Executive Engineer
Municipal Corporation
Bhilai


Assistant Engineer
Municipal Corporation
Bhilai


Sub Engineer
Municipal Corporation
Bhilai